

1. Report No. FHWA-01/1520-1		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle PENDULUM IMPACT TESTS ON BRIDGE DECK SECTIONS				5. Report Date December 2000 Resubmitted: July 2001	
				6. Performing Organization Code	
7. Author(s) David Trejo, Francisco Aguiniga, Eugene C. Buth, Ray W. James, and Peter B. Keating				8. Performing Organization Report No. Report 1520-1	
9. Performing Organization Name and Address Texas Transportation Institute The Texas A&M University System College Station, Texas 77843-3135				10. Work Unit No. (TRAIS)	
				11. Contract or Grant No. Project No. 9-1520	
12. Sponsoring Agency Name and Address Texas Department of Transportation Construction Division Research and Technology Transfer Section P. O. Box 5080 Austin Texas 78763-5080				13. Type of Report and Period Covered Letter Report: August 1999 – April 2000	
				14. Sponsoring Agency Code	
15. Supplementary Notes Research performed in cooperation with U. S. Department of Transportation, Federal Highway Administration. Research Project Title: FRP Reinforcing Bars in Bridge Decks					
16. Abstract  Fiber-reinforced polymers (FRP) are being increasingly used in the construction industry. One application is to use FRP bars as reinforcement in concrete. This report presents a study of the behavior of bridge deck overhangs built with FRP bars when subjected to pendulum impact forces. Researchers tested four specimens. Two of the specimens were reinforced with conventional steel bars, and two were reinforced with FRP bars. This report presents a comparison between the results obtained with the two systems.					
17. Key Words FRP, Concrete, Impact			18. Distribution Statement No restrictions. This document is available to the public through NTIS: National Technical Information Service 5285 Port Royal Road Springfield, Virginia 22161		
19. Security Classif.(of this report) Unclassified		20. Security Classif.(of this page) Unclassified		21. No. of Pages 31	22. Price



# **PENDULUM IMPACT TESTS ON BRIDGE DECK SECTIONS**

by

David Trejo  
Assistant Professor  
Texas A&M University

Francisco Aguiniga  
Research Assistant  
Texas Transportation Institute

C. Eugene Buth  
Director of Impact Test Facility  
Texas Transportation Institute

Ray W. James  
Manager, Major Highway Structures Program  
Texas Transportation Institute

and

Peter B. Keating  
Associate Professor  
Texas A&M University

Report 1520-1  
Project Number 9-1520  
Research Project Title: FRP Reinforcing Bars in Bridge Decks

Sponsored by the U. S. Department of Transportation  
Federal Highway Administration

December 2000  
Resubmitted: July 2001

TEXAS TRANSPORTATION INSTITUTE  
The Texas A&M University System  
College Station, Texas 77843-3135



## **DISCLAIMER**

The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official view or policies of the U. S. Department of Transportation. This report does not constitute a standard, specification or regulation.

## ACKNOWLEDGMENTS

Research performed in cooperation with the U. S. Department of Transportation, Federal Highway Administration, and partial support for the second author, Francisco Aguiniga, provided by the Consejo Nacional de Ciencia y Tecnología.

The authors wish to express their gratitude to:

Ronald E. Koester, P.E., TxDOT, Waco District  
Project Coordinator

Timothy E. Bradberry, P.E., TxDOT, Bridge Division  
Project Director

Project Advisors:

Don Harley, P.E., Federal Highway Administration

Mary Lou Ralls, P.E., TxDOT, Bridge Division

Joe Chappell, P.E., TxDOT, Amarillo District

Mark Bloschock, P.E., TxDOT, Bridge Division

Kevin Pruski, P.E., TxDOT, Bridge Division

Robert Sarcinella, TxDOT, Construction Division

Paul McDad, TxDOT, Construction Division

## TABLE OF CONTENTS

List of Figures .....	viii
I. Objective.....	1
II. Specimen Description, Materials, and Equipment.....	1
Steel-Reinforced Specimens .....	1
Hybrid Specimens.....	2
Impact Pendulum .....	2
III. Test Method .....	3
IV. Test Results.....	3
Steel-Reinforced Specimens .....	3
Progressive Impact.....	3
Single Impact .....	4
Hybrid Specimens.....	5
Progressive Impact.....	5
Single Impact .....	5
Summary of Test Results.....	6
V. Conclusions and Recommendations .....	7
VI. Blueprints.....	9
VII. Photographs.....	17
VIII. References.....	23

## LIST OF FIGURES

Figure	Page
1. Specimen and Pendulum Setup.....	17
2. Specimen and Pendulum Setup.....	17
3. Specimen and Pendulum Setup.....	18
4. Steel-Reinforced Specimen, Progressive Impact Loading.....	18
5. Steel-Reinforced Specimen, Single Impact Loading.....	19
6. Steel-Reinforced Specimen, Single Impact Loading.....	19
7. Hybrid Specimen, Progressive Impact Loading.....	20
8. Hybrid Specimen, Progressive Impact Loading.....	20
9. Hybrid Specimen, Single Impact Loading.....	21
10. Hybrid Specimen, Single Impact Loading.....	21



## **I. OBJECTIVE**

The objective of the pendulum impact test is to determine whether or not Texas Department of Transportation should execute a change order to replace the glass-fiber-reinforced-polymer (GFRP) bars in the top mat of the slab overhangs of the Sierrita de la Cruz Creek Bridge with epoxy-coated steel bars. In addition to that, researchers will evaluate the performance of the barrier with regard to safety.

## **II. SPECIMEN DESCRIPTION, MATERIALS, AND EQUIPMENT**

The specimens are models of a representative section of the concrete deck of the Sierrita de la Cruz Creek Bridge. Researchers built and tested two sets of two identical specimens. One set is identified in this report as steel-reinforced specimens and the other as hybrid specimens.

### **STEEL-REINFORCED SPECIMENS**

These specimens are 600 mm (23.6 in.) wide and 200 mm (7.87 in.) deep concrete slabs, with a cantilever length of 720 mm (28.3 in.). A standard T-201 rail was built on the cantilever end.

These specimens were reinforced with 16 mm (0.625 in.) diameter epoxy-coated steel rebars in the top and bottom mats in both directions, with the bar spacings shown in blueprints 1 and 2.

## **HYBRID SPECIMENS**

These specimens are 560 mm (22 in.) wide and 200 mm (7.87 in.) deep slabs, with a cantilever length of 720 mm (28.3 in.). The moment of inertia of the hybrid specimens is 93 percent of the moment of inertia of the steel-reinforced specimens. A standard T-201 rail was built on the cantilever end.

These specimens were reinforced with 16 mm (0.625 in.) diameter epoxy-coated steel bars in the bottom mat, and GFRP rebars in the top mat in both directions, with the bar sizes and spacings shown in blueprints 3 and 4.

After placing the reinforcement, strain gages were installed in all specimens on the two central top bars oriented in the direction perpendicular to the bridge traffic.

The concrete specified for the deck was class “S,” with a specified 28-day strength of 28 MPa (4000 psi) in all specimens. On the other hand, the concrete specified for the rail was class “C,” with a specified 28-day strength of 25 MPa (3600 psi).

## **IMPACT PENDULUM**

Researchers tested the specimens at the Texas Transportation Institute (TTI) facilities located on the Riverside Campus of the Texas A&M University System. The pendulum used to hit the specimens has a mass of 820 kg (1808 lb). A description of the pendulum can be found in reference 1. The pendulum mass has an accelerometer installed on it, and the accelerometer is connected to a data acquisition system that records the acceleration of the mass at time intervals of 0.0005 sec.

The setup of the specimens and pendulum are shown in Figures 1 to 3.

### III. TEST METHOD

Researchers conducted the tests as follows. The first steel-reinforced specimen was hit with a single blow of the pendulum. The second steel-reinforced specimen was hit multiple times, with incremental pendulum load levels, until reaching a load similar to the one that failed the first specimen.

The first hybrid specimen was subjected to incremental pendulum load levels until failure was attained. Then, the second hybrid specimen was hit with a single blow.

### IV. TEST RESULTS

The compressive strength of the concrete specimens, as determined by compression tests on the day of the test, is shown in Table 1.

**Table 1. Concrete Cylinder Compressive Strength.**

Specimen		Concrete Cylinder Compressive Strength at Indicated Age MPa (psi).				
		Concrete Age (days)				
		7	13	14	27	28
Steel	Deck	25.5 (3702)	32.0 (4638)	33.0 (4790)*	-----	32.9 (4768)
	Rail	25.7 (3729)	28.2 (4089)*	24.8 (3593)	-----	30.9 (4484)
GFRP	Deck	25.4 (3683)	-----	29.5 (4282)	-----	35.4 (5140)*
	Rail	19.9 (2888)	-----	20.1 (2914)	27.6 (4004)*	26.0 (3767)

\* Concrete cylinder compressive strength on the day of the impact test.

### STEEL-REINFORCED SPECIMENS

#### Progressive Impact

**Impact Force** Researchers recorded the impact forces for every test. These values were 25.0 kN (5.62 Kip) for the first impact, 34.1 kN (7.67 Kip) for the second impact, 42.4 kN (9.53 Kip) for the third impact, and 51.2 kN (11.5 Kip) for the last impact. All forces were back calculated from the acceleration records.

**Cracking Pattern** Figure 4 shows the cracking pattern. After applying the maximum load, the specimen showed two cracks running parallel to the rail at the top of the slab.

**Maximum Bar Strain and Bar Force** The maximum strain recorded in the bars was 1600  $\mu$ . Blueprint 1 shows the strain gage location. The maximum bar's force attained was 64.1 kN (14.4 Kip).

**Rail Rotation** The rotation of the rail with respect to the end of the cantilever, measured after impact, was 6 °.

### **Single Impact**

**Maximum Impact Force** The maximum impact force recorded was 55.2 kN (12.4 Kip). This force was back calculated from the acceleration records.

**Cracking Pattern** The cracking pattern is shown in Figures 5 and 6. After applying the maximum load, the specimen showed two cracks running parallel to the rail at the top of the slab.

**Maximum Bar Strain and Bar Force** The maximum strain recorded in the bars was 1250  $\mu$ . The strain gage location is shown in blueprint 1. The maximum bar's force attained was 49.8 kN (11.2 Kip).

**Rail Rotation** The rotation of the rail with respect to the end of the cantilever, measured after impact, was 11.5 °.

## **HYBRID SPECIMENS**

### **Progressive Impact**

**Impact Force** The impact forces recorded for every test were 24.2 kN (5.43 Kip) for the first impact, 33.0 kN (7.42 Kip) for the second impact, 42.8 kN (9.63 Kip) for the third impact, and 40.2 kN (9.04 Kip) for the last impact. All forces were back calculated from the acceleration records.

**Cracking Pattern** Figures 7 and 8 show the cracking pattern. After applying the maximum load, the specimen showed three cracks running parallel to the rail at the top of the slab.

**Maximum Bar Strain and Bar Force** The maximum strain recorded in the bars was 3580  $\mu$ . The strain gage location is shown in blueprint 3. The maximum bar's force attained was 40.4 kN (9.09 Kip).

**Rail Rotation** The rotation of the rail with respect to the end of the cantilever, measured after impact, was 10.5 °.

### **Single Impact**

**Maximum Impact Force** The maximum impact force recorded was 53.4 kN (12.0 Kip). This force was back calculated from the acceleration records.

**Cracking Pattern** Figures 9 and 10 show the cracking pattern. After applying the maximum load, the specimen showed two cracks running parallel to the rail at the top of the slab.

**Maximum Bar Strain and Bar Force** The maximum strain recorded in the bars was 2800  $\mu$ . The strain gage location is shown in blueprint 3. The maximum bar's force attained was 31.7 kN (7.12 Kip).

**Rail Rotation** The rotation of the rail with respect to the end of the cantilever, measured after impact, was 19 °.

## SUMMARY OF TEST RESULTS

Table 2 presents a comparison of the performance of the hybrid specimens relative to the steel-reinforced specimens. The modulus of elasticity of the steel bars was assumed to be 200 GPa ( $29 \times 10^6$  psi). The modulus of elasticity of the GFRP bars was taken from a brochure provided by the rebar manufacturer, where the modulus has a value of 40 GPa ( $5.77 \times 10^6$  psi.)

**Table 2. Performance of Specimens.**

Maximum Parameter		Steel-Reinforced Specimen	Hybrid Specimen	Hybrid/Steel
Single Impact	Load, kN (Kip)	55.2 (12.4)	53.4 (12.0)	0.97
	Bar Strain, $\mu$	1250	2800	2.24
	Bar Force, kN (Kip)	49.8 (11.2)	31.7 (7.12)	0.64
	Rail Tip Rotation (degrees)	11.5	19	1.65
Progressive Impact	Load, kN (Kip)	51.2 (11.5)	42.8 (9.63)	0.84
	Bar Strain, $\mu$	1600	3580	2.23
	Bar Force, kN (Kip)	64.1 (14.4)	40.4 (9.09)	0.63
	Rail Tip Rotation (degrees)	6	10.5	1.75

## V. CONCLUSIONS AND RECOMMENDATIONS

The maximum loads imposed on the hybrid specimens were 3 and 16 percent less than the loads imposed on the steel-reinforced specimens, under single and progressive impact loadings, respectively. The strains in the GFRP bars of the hybrid specimens are over 200 percent higher than the strains recorded in the top bars of the steel-reinforced specimens. However, the maximum force developed in the GFRP bars of the hybrid specimens was only 64 percent of the force developed in the epoxy-coated steel bars of the steel-reinforced specimens. Finally, the rail tip rotation was about 70 percent larger for the hybrid specimens than it was for the steel-reinforced specimens.

The top rebars, perpendicular to the traffic direction, play a major role in restraining the lateral and downward deflections, as well as the rotations of the rail. Due to lower axial and flexural elastic moduli of the GFRP rebars, the hybrid specimens rotate and deflect more than the steel-reinforced specimens. In this regard, the GFRP bars of the single impact hybrid specimen showed breaking of some glass fibers due to flexure. However, after applying the maximum force to all the hybrid specimens, the rail stayed attached to the deck and could be climbed on and examined without any indication of further movement or instability, similar to the steel-reinforced specimens.


Based on the above results, the research team concludes that the use of GFRP rebars, as indicated in the blueprints of the Sierrita de la Cruz Creek Bridge, grants adequate performance of the system regarding rail safety. Therefore, it is deemed unnecessary to use additional epoxy-coated steel rebars on the top mat in the direction perpendicular to traffic. However, researchers will still conduct a full crash test to examine the behavior of the system in an actual traffic situation.

It is also noted that the hybrid specimens showed excellent performance in the region of maximum moment of the cantilever.






VI. BLUEPRINTS




TEST INSTALLATION PLAN




NOTE: ALL LONGITUDINAL STEEL 550mm LONG.


SECTION A-A




BACK TUBE DETAIL 2 PLAN & ELEVATION



SIDE VIEW (TRAFFIC FACE)



FRONT TUBE DETAIL 1 PLAN & ELEVATION




C150 X 12 DETAIL 3 PLAN


NOTES:

- 1.) ALL REINFORCING STEEL SHALL BE GRADE 420 (60KSI).
- 2.) ALL STRUCTURAL STEEL SHALL BE A36 MATERIAL.
- 3.) CONCRETE USED FOR DECK SHALL BE TXDOT CLASS "S" CONCRETE (4000 PSI)
- 4.) CONCRETE USED FOR RAIL SHALL BE TXDOT CLASS "C" (3600PSI).


The Texas A&M University System					
TEXAS TRANSPORTATION INSTITUTE COLLEGE STATION, TEXAS 77843					
Revisions		Project No.	Date	Drawn By	Scale
No.	Date				
1.		TXDOT STEEL REINFORCING BARS IN BRIDGE DECKS		Sheet No.	1 of 2
2.		PENDULUM TEST INSTALLATION			
3.					
4.					
5.					




#4 STIRRUP (BARE STEEL)  
DETAIL 4




"V" BARS (#5)  
EPOXY COATED  
DETAIL 7




"W" BARS (#4)  
EPOXY COATED  
DETAIL 8




#5 EPOXY COATED  
DETAIL 5



#5 EPOXY COATED  
DETAIL 6



#4 EPOXY COATED  
AND BARE STEEL  
DETAIL 9




#5 EPOXY COATED  
AND BARE STEEL  
DETAIL 10


The Texas A&M University System				
TEXAS TRANSPORTATION INSTITUTE COLLEGE STATION, TEXAS 77843				
Revisions		Project No.	Date	Drawn By
No.	Date	By		
1.			425200	01/00
2.			WFW	
3.				
4.				
5.				
TXDOT STEEL REINFORCING BARS IN BRIDGE DECKS				Scale
PENDULUM TEST INSTALLATION				Sheet No.
				2 of 2

Mar 24, 2000 - 1:18pm

T:\AutoCad Drawings\425200\T201 penSTLREBAR.dwg




TEST INSTALLATION PLAN




SECTION A-A


NOTE: ALL LONGITUDINAL REINFORCEMENT 510mm LONG.




BACK TUBE  
DETAIL 2  
PLAN & ELEVATION



SIDE VIEW  
(TRAFFIC FACE)



FRONT TUBE  
DETAIL 1  
PLAN & ELEVATION



C150 X 12  
DETAIL 3  
PLAN


NOTES:

- 1.) ALL REINFORCING STEEL SHALL BE GRADE 420 (60KSI).
- 2.) ALL STRUCTURAL STEEL SHALL BE A36 MATERIAL.
- 3.) CONCRETE USED FOR THE DECK SHALL BE TXDOT CLASS "S" CONCRETE (4000 PSI)
- 4.) CONCRETE USED FOR THE RAIL SHALL BE TXDOT CLASS "C" (3600 PSI)
- 5.) FOR GFRP REINFORCEMENT, USE TAN, SPIRALED "CANDY CANE" BARS IN TTI STOCK.


The Texas A&M University System				
Revisions				
No.	Date	By		
1.				
2.				
3.				
4.				
5.				
6.				

TEXAS TRANSPORTATION INSTITUTE COLLEGE STATION, TEXAS 77843			
Project No.	Date	Drawn By	Scale
425200	01/00	WFW	
TXDOT GFRP REINFORCING BARS IN BRIDGE DECK PENDULUM TEST INSTALLATION			Sheet No. 1 of 2




#4 STIRRUP (BARE STEEL)  
DETAIL 4




"V" BARS (#5)  
EPOXY COATED  
DETAIL 7


"W" BARS (#4)  
EPOXY COATED  
DETAIL 8




#6 GFRP BAR  
DETAIL 5



#5 EPOXY COATED  
DETAIL 6



#4 BARE STEEL  
DETAIL 9



#5 EPOXY COATED  
AND GFRP  
DETAIL 10

The Texas A&M University System			
Revisions		TEXAS TRANSPORTATION INSTITUTE COLLEGE STATION, TEXAS 77843	
No.	Date	By	
1.			
2.			
3.			
4.			
5.			
Project No. 425200		Date 01/00	Drawn By WFW
TXDOT GFRP REINFORCING BARS IN BRIDGE DECK		Sheet No. 2 of 2	
PENDULUM TEST INSTALLATION			

Mar 24, 2000 - 1:06pm

T:\AutoCad Drawings\425200\T201.pcn\GFRPREBAR.dwg

## VII. PHOTOGRAPHS






Figure 1. Specimen and Pendulum Setup.




Figure 2. Specimen and Pendulum Setup.



**Figure 3. Specimen and Pendulum Setup.**




**Figure 4. Steel-Reinforced Specimen, Progressive Impact Loading.**




**Figure 5. Steel-Reinforced Specimen, Single Impact Loading.**



**Figure 6. Steel-Reinforced Specimen, Single Impact Loading.**




**Figure 7. Hybrid Specimen, Progressive Impact Loading.**




**Figure 8. Hybrid Specimen, Progressive Impact Loading.**





**Figure 9. Hybrid Specimen, Single Impact Loading.**



**Figure 10. Hybrid Specimen, Single Impact Loading.**

## VIII. REFERENCES

- [1] Zimmer, R.A., and Althea G. A., *Calibration of the TTI 820 kg Pendulum*, Texas Transportation Institute, June 1997.