



TECHNICAL REPORT 0-6806-CTR-R6
TxDOT PROJECT NUMBER 0-6806-CTR

Literature Review on Use of Nanoparticle Technology for Reducing Emissions

Lisa Loftus-Otway

August 2019; Published July 2021

<http://library.ctr.utexas.edu/ctr-publications/0-6806-CTR-R6.pdf>



Technical Report Documentation Page

1. Report No. FHWA/TX-19/0-6806-CTR-R6		2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Literature Review on Use of Nanoparticle Technology for Reducing Emissions			5. Report Date August 2019; Published July 2021	
			6. Performing Organization Code	
7. Author(s) Lisa Loftus-Otway			8. Performing Organization Report No. 0-6806-CTR-R6	
9. Performing Organization Name and Address Center for Transportation Research The University of Texas at Austin 3925 W. Braker Lane, 4th floor Austin, TX 78759			10. Work Unit No. (TRAIS)	
			11. Contract or Grant No. 0-6806-CTR	
12. Sponsoring Agency Name and Address Texas Department of Transportation Research and Technology Implementation Division P.O. Box 5080 Austin, TX 78763-5080			13. Type of Report and Period Covered Technical Report January 2019–August 2019	
			14. Sponsoring Agency Code	
15. Supplementary Notes Project performed in cooperation with the Texas Department of Transportation and the Federal Highway Administration.				
16. Abstract Nanoscale science, engineering, chemistry and technology—nanotechnology science—is expected to deliver societal and economic benefits in multiple fields. Transportation is expected to be one of the sectors that will see impacts from improved material life through to environmental benefits. This report provides a high-level overview and introduction to the science of nanotechnology, reviews the federal role and funding for nanotechnology, and outlines national-level research, initiatives, and organizations. Also provided is a high-level overview of current topics of nanotechnology research and development (R&D) in transportation infrastructure, including its use to achieve emissions reductions.				
17. Key Words Nanotechnology, emissions, infrastructure			18. Distribution Statement No restrictions. This document is available to the public through the National Technical Information Service, Springfield, Virginia 22161; www.ntis.gov .	
19. Security Classif. (of report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of pages 68		22. Price



**THE UNIVERSITY OF TEXAS AT AUSTIN
CENTER FOR TRANSPORTATION RESEARCH**

Literature Review on Use of Nanoparticle Technology for Reducing Emissions

Lisa Loftus-Otway

CTR Technical Report:	0-6806-CTR-6
Report Date:	August 2019; Published July 2021
Project:	0-6806-CT
Project Title:	TxDOT Administration Research
Sponsoring Agency:	Texas Department of Transportation
Performing Agency:	Center for Transportation Research at The University of Texas at Austin

Project performed in cooperation with the Texas Department of Transportation and the Federal Highway Administration.

Disclaimers

Author's Disclaimer: The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official view or policies of the Federal Highway Administration or the Texas Department of Transportation (TxDOT). This report does not constitute a standard, specification, or regulation.

Patent Disclaimer: There was no invention or discovery conceived or first actually reduced to practice in the course of or under this contract, including any art, method, process, machine manufacture, design or composition of matter, or any new useful improvement thereof, or any variety of plant, which is or may be patentable under the patent laws of the United States of America or any foreign country.

Notice: The United States Government and the State of Texas do not endorse products or manufacturers. If trade or manufacturers' names appear herein, it is solely because they are considered essential to the object of this report.

Engineering Disclaimer

NOT INTENDED FOR CONSTRUCTION, BIDDING, OR PERMIT PURPOSES.

Acknowledgments

CTR thanks the Research and Technology Implementation Division for supporting this research project.

Table of Contents

Chapter 1. Summary	1
Chapter 2. Nanotechnology: An Introduction.....	4
2.1. Overview of Nanotechnology Science	4
2.2. Federal Role and Investment	7
2.3. National Research Initiatives and Organizations.....	10
2.3.1. The National Nanotechnology Initiative.....	10
Chapter 3. Nanotechnology in Transportation Infrastructure	12
3.1. Literature Review Approach and Methodology	12
3.2. Overview of Current Topics of Nanotechnology R&D in Transportation Infrastructure	14
3.2.1. U.S. Patent Applications	37
3.2.2. The Hype Around Nanotechnology and Emission Reduction.....	38
References	42
Appendix A.....	45

List of Figures

Figure 1.1 Nitric Oxide Removal Efficiency Results	3
Figure 2.1 The Top-Down and Bottom-Up Approaches in Nanotechnology.....	5
Figure 2.2 NNI Funding in Current Dollars, FY2001–2017	8
Figure 2.3 Agency Allocations from NNI Budget Appropriations.....	8
Figure 2.4 Funding Investment Gap in the Manufacturing-Innovation Process.....	9
Figure 2.5 Manufacturing Innovation: Investment Gap	9
Figure 2.6 Structure of NNI	11
Figure 3.1 Particle Size and Specific Surface Area Related to Concrete Materials	17
Figure 3.2 Degradation Rates as a Function of NO Content on Concrete Paving.....	18
Figure 3.3 Results for Static Chamber Reduction in Toluene and TMB after 120 Minutes	21
Figure 3.4 Results for NO Reduction after 30 Minutes with Flow-through Chamber Data and Converted to Static Chamber Data	22
Figure 3.5 Degradation rate of CO, CO ₂ , NO _x , HC under catalysis of TiO ₂ doped with respectively 0.1%, 0.05%, 0.01% F3+ and unmodified TiO ₂	23
Figure 3.6 NO Removal Efficiencies for Original, Worn, and Abraded Samples.....	25
Figure 3.7 Effect of GGBFS as Cement Replacement and PCAT Concrete Cover on Annual Cost.....	26
Figure 3.8 Influence of NO _x Degradation Rate and PCAT Cover Thickness on Annual Cost.....	27
Figure 3.9 Effects of the Depth of TiO ₂ and Void Ratio on NO _x Reduction Efficiency	29
Figure 3.10 NO Removal Efficiency Results	35
Figure 3.11 Durability Results.....	35
Figure 3.12 NO Conversion Degree Using Photocatalytic Coating with TiO ₂	36
Figure 3.13 United States Patent Application.....	38

List of Tables

Table 3.1 Websites Visited	13
Table 3.2 Definitions of Concrete and Nanotechnology in Concrete	16
Table 3.3 Summary of Results for Each Application Type Before Abrasion	21
Table 3.4 Material Cost & Observed In-Lab Pollutant Reduction for Each Coating Type.....	22
Table 3.5 Annual Cost of Base Case Accounting for NO _x and PM ₁₀ Degradation.....	26
Table 3.6 Preparation of Three Coating Solutions.....	34
Table 3.7 Test Groups.....	34
Table A1: Journal Articles on Nanotechnology.....	45
Table A2: Journal Items on Non-Nano Techniques for Emissions Reduction	57

Chapter 1. Summary

Nanoscale science, engineering, chemistry, and technology—which the Congressional Research Service in a 2016 primer (CRS, 2016) refers to “nanotechnology science”—is expected to deliver societal and economic benefits in multiple fields. Transportation is expected to be one of the sectors that will see impacts from improved material life through to environmental benefits.

Nanotechnology operates at the scale of 1 to 100 nanometers (one nanometer = billionth of a meter). Properties of matter at this size are fundamentally different than the properties of individual atoms and molecules. Nanoscale materials have far larger surface areas than similar masses of larger-scale materials. This means that as surface area per mass of a material increases at the nanoscale, a greater amount of the nanoscale material can come into contact with surrounding materials, thus affecting reactivity. In the case of titanium dioxide (TiO_2) applied to concrete to create photocatalytic concrete, this greater surface area allows the remediation of carbon dioxide (CO_2), nitrogen oxides (NO_x), and other chemicals when the surface is exposed to ultraviolet (UV) rays from sunlight. When rain (or water that is applied) reacts with the TiO_2 and UV light, it undergoes a chemical change and allows the pollutants to, in essence, wash away.

Nanotechnology is derived from two main approaches: the “top-down” approach, wherein larger structures are reduced in size to the nanoscale but maintain their original properties without atomic-level control (for example, electronics miniaturization) or are deconstructed from larger structures into their smaller, composite parts; and secondly the “bottom-up” approach, also called “molecular nanotechnology” or “molecular manufacturing,” wherein materials are engineered from atoms or molecular components through a process of assembly/self-assembly

Much of the current technology developments and applications are incremental—some say evolutionary—in nature, offering what seem like very modest improvements. Nanotechnology is playing a current substantive fundamental role in microchips and storage density of memory in computing.


At the federal level, the United States Congress began supporting research and development (R&D) in 2000. Funding began in 2001 when the U.S. Congress appropriated just under \$500 million for agencies conducting nanotechnology work. In 2003 the U.S. Congress passed the 21st Century Nanotechnology Research and Development Act of 2003 (Public Law 108-153, 15 USC §7501). The law authorized the legislative foundation for the National Nanotechnology Initiative (NNI). The President’s 2018 budget provided for \$1.2 billion in support to the NNI. Nanotechnology research has been directed to three major topic areas: federal R&D investments, U.S. international competitiveness and environment, and health and safety concerns. According to the Congressional Research Service, the U.S. is estimated to account for approximately a third of total global nanotechnology R&D.

To date there has been a plethora of research into nanotechnology in multiple fields. For nanotechnology specifically in transportation and emissions reduction, much of the focus has been on tailpipe emission reduction through the use of nanomaterials. For the purposes of this literature review, however, research into nanotechnology for use in transportation infrastructure to gain emissions reductions has primarily focused on concrete and the use of nano TiO₂.

The literature review went through an interactive process. The CTR library staff (who assisted in this process) used databases at UT Austin and found that simply typing in “nanotechnology” or “nanomaterials with emissions reductions” brought up thousands of journal articles not relevant to the subject matter of this report. After a series of keyword shuffles, the CTR library staff narrowed down key words, arriving at a list of 400+ articles. Some 200 were downloaded, read, and reviewed, and approximately 70 are discussed in this report. What is clear is that much R&D needs to be conducted to determine how nano TiO₂ can be utilized at a commercial scale on concrete and asphalt pavements. While considerable research has been conducted, and this product is commercially available, it is neither cheap nor ubiquitously used. Research being conducted right now is still discovering the multitude of combinations, properties, longevity, and durability of different application methods of this product in a laboratory setting and in small field trials.

As in many new disruptive technologies, there is still some hype over the benefits of nanomaterials and products. One study noted “*Results showed that increasing load cycles, photocatalytic activity of sprayed material is reduced up to half of the initial value*” and the Government Accountability Office (GAO) has stated that “*The extent to which nanomaterials present a risk to human health and the environment depends on a combination of the toxicity of specific nanomaterials and the route and level of exposure to these materials. Although the body of research related to nanomaterials is growing, the current understanding of the risks posed by these materials is limited*” (GAO, 2010). The GAO also noted that the Environmental Protection Agency “*faces challenges in effectively regulating nanomaterials that may be released in air, water, and waste because it lacks the technology to monitor and characterize these materials or the statutes include volume based regulatory thresholds that may be too high for effectively regulating the production and disposal of nanomaterials*” (GAO, 2010).

Notwithstanding these cautionary components, the research reviewed revealed significant promise in the ability of just one nano product—nano titanium dioxide—to reduce multiple types of pollutants at a significant level, sometimes up to 60 to 70%, on both concrete and asphalt pavements and in barriers and sound walls. Figure 1.1 shows nitric oxide removal efficiency using TiO₂.



Source: Leng et al., 2018

Figure 1.1 Nitric Oxide Removal Efficiency Results

Doubtless, as technologies improve and become cheaper, opportunities will arise to enable use of such materials, even after infrastructure is built.

Areas of further research into the use of nanomaterials for storm water and water runoff also show some promise, as current research is looking at nanotechnology to break down and biodegrade components within sewage and waste water.

Finally, other areas that may also provide impetus for cross-pollination of research for transportation infrastructure may also come out of the Department of Energy and the Department of Defense's large R&D budget allocations for nanotechnology.

Chapter 2. Nanotechnology: An Introduction

This chapter will cover three main topic areas:

1. Introduction and overview to nanotechnology
2. The federal role and current investment
3. National level research, initiatives, and organizations

2.1. Overview of Nanotechnology Science

As noted, nanotechnology science is expected to deliver societal and economic benefits in multiple fields.

Nanotechnology operates at the scale of 1 to 100 nanometers (one nanometer = billionth of a meter). Nanoscale occurs naturally in nature. For example, hemoglobin is 5.5 nanometers in diameter, one strand of DNA is 2 nanometers in diameter, and a human hair is 80,000 nanometers in diameter. Properties of matter at this size are fundamentally different than the properties of individual atoms and molecules. According to the National Nanotechnology Initiative (NNI),

“when particles are created with dimensions of about 1–100 nanometers (where the particles can be “seen” only with powerful specialized microscopes), the materials’ properties change significantly from those at larger scales. This is the size scale where so-called quantum effects rule the behavior and properties of particles. Properties of materials are size-dependent in this scale range. Thus, when particle size is made to be nanoscale, properties such as melting point, fluorescence, electrical conductivity, magnetic permeability, and chemical reactivity change as a function of the size of the particle.”


As a consequence of these properties, nanoscale materials have far larger surface areas than similar masses of larger-scale materials. This means that as surface area per mass of a material increases at the nanoscale, a greater amount of the nanoscale material can come into contact with surrounding materials, thus affecting reactivity. In the case of titanium dioxide (TiO_2) applied to concrete to create photocatalytic concrete, this greater surface area allows the remediation of CO_2 and NO_x and other chemicals when the surface is exposed to ultraviolet (UV) rays from sunlight. When rain (or water that is applied) reacts with the TiO_2 and UV light, it undergoes a chemical change and allows the pollutants to, in essence, wash away.

In a 2012 report the GAO noted that:

“Nanomaterials come in a variety of forms based both on their chemical composition and physical structure. For example, carbon-based nanomaterials can be produced in a number of physical structures such as sheets (graphene), tubes (carbon nanotubes), and particles (carbon black). Nanomaterials can enter the marketplace as materials themselves, as

intermediates that either have nanoscale features or incorporate nanomaterials, and as final nano-enabled products” (GAO 12-427, 2012).

Nanotechnology is derived from two main approaches according to Sanchez and Sobolev (2010). Firstly, in the “top-down” approach, larger structures are reduced in size to the nanoscale but maintain their original properties without atomic-level control (for example, electronics miniaturization) or are deconstructed from larger structures into their smaller, composite parts. Secondly, in the “bottom-up” approach (also called “molecular nanotechnology” or “molecular manufacturing”), materials are engineered from atoms or molecular components through a process of assembly/self-assembly (Sanchez and Sobolev, 2010). Figure 2.1 shows the two processes.



Source: Sanchez and Sobolev, 2010

Figure 2.1 The Top-Down and Bottom-Up Approaches in Nanotechnology

Nano material types fall into four main categories (GAO 10-549, 2010).

“Carbon-based materials. These nanomaterials are composed mostly of carbon, and are most commonly spherical, elliptical, or tubular in shape. Spherical and elliptical carbon shapes are referred to as fullerenes, while tubular ones are called nanotubes.

Metal-based materials. These nanomaterials include nanoscale gold, nanoscale silver, and metal oxides, such as TiO₂. They also include quantum dots, which are closely packed semiconductor crystals comprised of hundreds or thousands of atoms, on the scale of a few nanometers to a few hundred nanometers.

Dendrimers. These nanomaterials are nanoscale polymers built from branched units. The surface of a dendrimer has numerous branch ends, which can be tailored to perform specific chemical functions. Also, some dendrimers contain interior cavities into which other molecules can be placed, such as for drug delivery.

Composites. These materials combine nanoparticles with other nanoparticles or with larger, conventional-scale materials. For example, nanoparticles, such as nanoscale clay

can be combined with other materials to form a composite material” (GAO 10-54p, 2010 pp 6).

Much of the current technology developments and applications are incremental—some say evolutionary—in nature, offering what seem like very modest improvements. The major areas where nanotechnology is playing a current substantive fundamental role is in microchips, and storage density of memory in computing. Consumer products that incorporate nanotechnology are currently found in the areas of clothing, cosmetics, household appliances, and sporting goods (GAO, 2012). A 2010 study by Roco et al. estimated that products enabled by nanotechnology would double every 3 years globally with an estimated \$3 trillion market and 6 million workers by 2020 (Roco et al., 2010). *Azonano* magazine estimates the global market for nanotechnology will exceed \$124 billion by 2024 (Cuffari, 2018).

Over the longer term, nanotechnology is anticipated to deliver major advances that may have profound implications for society as well benefits in the areas of:

- Detection and treatment of disease
- Renewable energy
- Water treatment
- Environmental remediation
- Emission reduction
- Agricultural and food applications
- Self-healing materials
- Toxin and pathogen sensors

Notwithstanding the excitement over the potential for nanotechnology to enhance and augment current processes, potential risks are expected to arise from exposure to nanomaterials during manufacture use and end-of-life disposal. The GAO noted:

“The use of nanomaterials in commercial applications raises questions about the potential risks that might arise from exposures to nanomaterials and the differences in exposure during their manufacture, use, and disposal. For example, some, but not all, research studies have shown adverse respiratory or cellular effects in animals exposed to some types of carbon nanotubes. Observed effects include early onset and persistence of pulmonary fibrosis and interference with cell division. The risk posed by a material is a combination of the hazard or negative effect that material may have on an organism and the extent of the organism’s exposure to that material. Therefore, a highly poisonous material—that is, one with high hazard—may nonetheless pose little risk if susceptible groups have little or

no contact with the material. For instance, many household chemicals are hazardous to human health but pose little risk when exposure is limited by safe handling. Conversely, a material with relatively mild health effects may pose a large risk if people or the environment are exposed to large amounts or over prolonged periods” (GAO 12-427, 2012).

2.2. Federal Role and Investment


The United States Congress began supporting R&D in 2000. Nanotechnology research has been directed to three major topic areas: federal R&D investments, U.S. international competitiveness and environment, and health and safety concerns.

Funding began in 2001 when the U.S. Congress appropriated just under \$500 million dollars for agencies conducting nanotechnology work. This rose to \$1.5 billion by 2017 (Figure 2.2). The President’s 2018 budget provided for \$1.2 billion in support to the NNI.

In 2003 the U.S. Congress passed the 21st Century Nanotechnology Research and Development Act of 2003 (Public Law 108-153, 15 USC §7501). The law authorized the legislative foundation for the NNI, established programs, and assigned agency responsibilities, along with setting funding approval levels for various federal agencies. The law, however, had some provisions that had expiration dates that have already passed. Attempts to develop comprehensive reauthorization of the act took place during the 110th through 114th Congress. These were unsuccessful. For example, during the 114th Congress, H.R. 1898 Subtitle B of the America Competes Reauthorization Act of 2015 (H.R. 1898) would have reauthorized the NNI; and The American Innovation and Competitiveness Act (S. 3084) would have modified certain NNI statutory reporting requirements. No bills have been introduced during in the 115th and the current 116th Congress.

According to the Congressional Research Service (CRS), the U.S. is estimated to account for approximately a third of total global nanotechnology R&D (CRS, 2016). Three federal agencies conduct nanotechnology R&D but also have regulatory responsibilities: the Environmental Protection Agency (EPA), Food and Drug Administration, and Consumer Product Safety Commission.

Figure 1. NNI Funding in Current Dollars, FY2001-FY2017




Source: CRS analysis of NNI data.

Source: CRS, 2016

Figure 2.2 NNI Funding in Current Dollars, FY2001–2017

Figure 2.3 depicts the split of funds by agencies since 2001. The U.S. Department of Transportation (USDOT) slice of this pie is very small compared to other agencies.



Source: NNI Website, not dated

Figure 2.3 Agency Allocations from NNI Budget Appropriations


The GAO in 2013 reported on a forum that was convened by the Comptroller General of the United States (GAO 14-181SP, 2014). This report noted two major funding and investments gaps, termed the “Valley of Death” and the “Missing Middle,” which had been identified by the President’s Council of Advisors on Science and Technology (PCAST) in July 2012.

The GAO definitions for these are the following:

“*The Valley of Death* refers to a gap in funding or investment that can occur after research on a new technology and its initial development—for example, when the technology moves beyond tests in a controlled laboratory setting. The term *Missing Middle* has been used to refer to the lack of funding/investment that can occur with respect to manufacturing


innovation—that is, maturing manufacturing capabilities and processes to produce technologies at scale innovation—that is, maturing manufacturing capabilities and processes to produce technologies at scale. Here, another important lack of support may be the absence of what one participant called an “industrial commons” to sustain innovation within a manufacturing sector. Logically, successful transitioning across the middle stages of manufacturing development is a prerequisite to achieving successful new approaches to manufacturing at scale.” (GAO, 14-181SP, 2014 pp 25-26),

Figure 2.4 shows where these gaps occur (GAO, 2014) and Figure 2.5 shows the original figure developed by PCAST.



Source: GAO, 14-181SP, 2014

Figure 2.4 Funding Investment Gap in the Manufacturing-Innovation Process



Source: PCAST, 2012

Figure 2.5 Manufacturing Innovation: Investment Gap

The GAO issued further reports in 2014 on nanomanufacturing, including one on nanomanufacturing and U.S. competitiveness in which testimony was given before the Subcommittee on Research and Technology; Committee on Science, Space, and Technology; U.S. House of Representatives (GAO, 14-618, 2014). This report noted that nano-based concrete was being heavily used, and that the U.S. had a 15% market share of chemical sales worldwide. The testimony noted, however, that:

“Experts offered differing views on U.S. global competitiveness in the commercialization and use of nanomaterials in concrete. A key forum participant said that while cement for domestic use is produced in the United States, today’s dominant companies—which are spearheading development of new technologies—are headquartered elsewhere (although this industry was previously dominated by the United States). Additionally, some experts said that other countries are spending more resources than the United States to promote commercialization; for example, one expert said that China established a national technology center to improve its competitiveness and domestic production of high-value, nano-based construction products” (GAO 14-618, 2014 pp6).

2.3. National Research Initiatives and Organizations


2.3.1. The National Nanotechnology Initiative

In 2000 President Clinton launched the NNI to coordinate all federal R&D activities and to promote U.S. competitiveness in this area. However, as noted above, overall federal funding has declined from a zenith in 2010, coupled with the lack of reauthorization of the 21st Century Nanotechnology Research and Development Act. While no specific funds were authorized as a consequence of the lack of reauthorization, Congress has continued to support the NNI with annual appropriations. The executive branch has also operated and reported on the NNI annually.

The NNI is coordinated within the White House through the National Science and Technology (NSET) Council subcommittee. The NSET subcommittee has 20 representatives from federal departments and agencies, the Office of Science and Technology Policy, and the Office of Management and Budget (OMB). The NSET subcommittee has two working groups: National Environmental and Health Implications, and Nanotechnology Innovation and Commercialization Ecosystem. Two previous working groups were eliminated (Global Issues in Nanotechnology and Nanotechnology Public Engagement and Communications). Figure 2.6 shows the NNI structure.

The NNI reports their research funding by area to the OMB as part of the annual budget process, although it should be noted that they do not report on project level data to the OMB.

The NNI has developed numerous strategic plans to identify categories of investments that are termed *Program Component Areas* (PCA). This provides a way to inform Congress and the executive branch on investments by area. The PCAs also cross-cut across individual agencies to aggregate up across thematic areas. The five current PCAs are Nanotechnology Signature Initiatives; Foundational Research; Nanotechnology-enabled Applications, Devices, and Systems; Research Infrastructure and Instrumentation; and Environment, Health, and Safety.



Source: NNI Website, not dated

Figure 2.6 Structure of NNI

Within the Nanotechnology Signature Initiatives PCA, dedicated funds are allocated for these specific and targeted focus areas:

- nanotechnology for solar energy collection and conversion
- sustainable nanomanufacturing
- nanoelectronics for 2020 and beyond
- nanotechnology knowledge infrastructure
- nanotechnology for sensor and sensors for nanotechnology

Transportation could take advantage of such dedicated funding across four of these areas currently, and nanoelectronics may be an area that will serve transportation in the future within automated and connected infrastructure and vehicles.

Chapter 3. Nanotechnology in Transportation Infrastructure

This chapter will cover these three topic areas:

1. Discussion on literature review methodology and approach.
2. Current R&D in nanotechnology use to achieve emissions reductions in transportation infrastructure.
3. The hype around nanotechnology.

3.1. Literature Review Approach and Methodology

A literature search was conducted using multiple database sites, with a time span back to 2000. This was done in an effort to reduce sources that were not relevant. The goal in this search was to find material that was pertinent and relevant. As explained in Chapter 1, simply typing in “nanotechnology” or “nanotechnology and emissions” returns an overwhelming number of results, not all of which are relevant. Keywords used included the following:

- Nanoparticle, air quality
- Nanotechnology and emission
- Nanotechnology, emission, and air quality
- Nanoparticle
- Concrete
- Reducing carbon emission with nanoparticles
- Reducing carbon emission with nanotechnology
- Nanoparticle + emission reduction + building + wrap
- Nanotechnology + emissions reduction
- Nanotechnology Co2 capture
- Nanotechnology climate change
- Nanomaterials could combat climate change and reduce pollution

Google Scholar searches were also conducted with these keywords:

- Building coatings to reduce emissions
- Building coating + emissions reduction

TxDOT noted at the outset of this literature review search request that at the Transportation Research Board's (TRB) Annual Meeting sessions were held on pavements and the urban climate (Session 1111), and decarbonizing transportation: advanced emissions controls (Session 1252). However, the online database from the annual meeting did not make available any PowerPoints or papers to review for these two sessions.

During the search period, CTR also reviewed the websites of the U.S. government, European Union, and other international groups and non-government organizations. The websites visited are listed in Table 3.1.

Table 3.1 Websites Visited

Entity	Type	URL
Whitehouse.gov	Office of President	https://www.whitehouse.gov/wp-content/uploads/2018/08/The-National-Nanotechnology-Initiative-Supplement-to-the-President%E2%80%99s-2019-Budget.pdf
National Nanotechnology Initiative	National U.S. federal organization.	https://www.nano.gov/
The National Academies	National Organization	http://www8.nationalacademies.org/onpinews/newsitem.aspx?RecordID=10395
United States Forest Service: R&D Nanotechnology	Federal Agency	https://www.fs.fed.us/research/nanotechnology/
US EPA	Federal Agency	https://www.epa.gov/sites/production/files/2015-01/documents/nanotechnology_whitepaper.pdf
CDC	Federal Agency	https://www.cdc.gov/niosh/topics/nanotech/faq.html
Virginia DOT	State DOT Nanotechnology of Concrete – conference	https://www.virginiadot.org/VDOT/Business/asset_upload_file772_3638.pdf
American Museum of Natural History	Education	https://www.amnh.org/learn-teach/curriculum-collections/young-naturalist-awards/winning-essays/2008/investigating-the-effect-of-silver-nanoparticles-on-aquatic-organisms
European Union	International Trading Block	http://ec.europa.eu/environment/integration/research/newsalert/pdf/75na3_en.pdf
World Economic Forum	International Organization	https://www.weforum.org/agenda/2015/07/5-ways-nanotechnology-can-tackle-climate-change/
OECD	International Organization	https://www.oecd-ilibrary.org/docserver/5k450q9j8p8q-

Entity	Type	URL
		en.pdf?expires=1563306945&id=id&accname=guest&checksum=6302979E613CAC04086CF4F3BCF70DD1 http://www.oecd.org/officialdocuments/publicdisplaydocumentpdf/?cote=DSTI/STP/NANO(2012)14&docLanguage=En https://www.oecd.org/science/nanosafety/44108334.pdf
ASEE	NGO	http://www.asee.org/documents/sections/2012/Midwest/ASEE Midwest 2012 Asmatulu Effects of.pdf
AIP 2018 Nano Innovation 2017 Conference Proceedings	Conference proceedings	https://aip.scitation.org/doi/pdf/10.1063/1.5047755
Azo Nano	Online journal	https://www.azonano.com/aboutus.aspx
Science Daily	Journal/newsfeed	https://www.sciencedaily.com/releases/2018/09/180927145555.htm
Nano Werk	Journal/Aggregator	https://www.nanowerk.com/
Center for Sustainable Nanotechnology	Institute	http://sustainable-nano.com/2016/02/02/nanotechnology-and-climate-change-finding-connections/
Institute of Development Studies	Institute	https://www.eldis.org/document/A42819
Foresight Institute	NGO	https://foresight.org/nanotechnology-vs-climate-change/
Electronic Privacy Information Center	NGO	https://epic.org/privacy/nano/
Sustainable Buildings initiative	NGO	https://sustainablebuildingsinitiative.org/toolkits/emissions-reduction-toolkits/energy-efficiency/office-design/?toolkit=97
Friends of the Earth	NGO	https://friendsoftheearth.uk/sites/default/files/downloads/nanotechnology_climate.pdf
IPEN	NGO	http://www.wecf.eu/download/2009/FINAL-OECDEnvironmentalBrief130709.pdf

3.2. Overview of Current Topics of Nanotechnology R&D in Transportation Infrastructure

The literature search revealed that while there is significant research in nanotechnology, narrowing this area down to transportation infrastructure specifically, and then to emissions reduction as a singular topic, reduced the number of pertinent items. The 2009 Nanotechnology in Construction Conference proceeding output (published in book form) noted that the construction industry is not

as dynamic as other industries, and that size and scale played a role (Nanotechnology in Construction, 2009). Tables A1 and A2 in the appendix list all the papers reviewed for this analysis.

The literature searches revealed significant research in the use of nanotechnology for tailpipe emission reduction, power plant emission remediation, indoor air conditioning filters that used nanotubes to capture multiple types of toxic compounds and gases, and the use of nanotechnology for water purification and for renewable energy—specifically in the coatings for solar panels and in the use of nanotechnology for greater conductivity in electric parts of solar arrays.

What was clear in the literature is that TiO_2 has been studied for over twenty years for its ability to reduce emissions when used in concrete and in asphalt. There was very little else in the literature regarding emission reduction using nano technology in transportation, aside from the expected plethora of research looking at emission reduction within the catalytic converter of an engine.

Haghighat et al. (Haghighat et al., 2019) reviewed the hydrothermal/solvothermal synthesis (HST) and treatment of for photocatalytic oxidation (PCO) of air pollutants, specifically focusing on the preparation, characterization, properties, and performance of TiO_2 for air purification. This critical review of HST for noted that:


“In order to advance PCO acceptability into large-scale application in air purification, it is crucial to develop more efficient and durable photocatalysts. Hence, synthetic methods with better control over physical and chemical characteristics of TiO_2 are of great importance. In this regard, hydrothermal/solvothermal technique has shown great promises by overcoming some of the most critical shortcomings of photocatalysts derived from other methods.”

Sanchez and Sobolev (Sanchez and Sobolev, 2010) give an excellent definition of nanotechnology and concrete. Table 3.2 provides their definitions.

Table 3.2 Definitions of Concrete and Nanotechnology in Concrete

Concrete: a complex, nano-structured material	Definition of nanotechnology in concrete
<p>“Concrete, the most ubiquitous material in the world, is a nanostructured, multi-phase, composite material that ages over time. It is composed of an amorphous phase, nanometer to micrometer size crystals, and bound water. The properties of concrete exist in, and the degradation mechanisms occur across, multiple length scales (nano to micro to macro) where the properties of each scale derive from those of the next smaller scale. The amorphous phase, calcium–silicate–hydrate (C–S–H) is the “glue” that holds concrete together and is itself a nanomaterial. Viewed from the bottom-up, concrete at the nanoscale is a composite of molecular assemblages, surfaces (aggregates, fibers), and chemical bonds that interact through local chemical reactions, intermolecular forces, and intraphase diffusion. Properties characterizing this scale are molecular structure; surface functional groups; and bond length, strength (energy), and density. The structure of the amorphous and crystalline phases and of the interphase boundaries originates from this scale. The properties and processes at the nanoscale define the interactions that occur between particles and phases at the microscale and the effects of working loads and the surrounding environment at the macroscale. Processes occurring at the nanoscale ultimately affect the engineering properties and performance of the bulk material.”</p>	<p>“The nanoscience and nano-engineering, sometimes called nanomodification, of concrete are terms that have come into common usage and describe two main avenues of application of nanotechnology in concrete research... <i>Nanoscience</i> deals with the measurement and characterization of the nano and microscale structure of cement-based materials to better understand how this structure affects macroscale properties and performance through the use of advanced characterization techniques and atomistic or molecular level modeling. <i>Nano-engineering</i> encompasses the techniques of manipulation of the structure at the nanometer scale to develop a new generation of tailored, multifunctional, cementitious composites with superior mechanical performance and durability potentially having a range of novel properties such as: low electrical resistivity, self-sensing capabilities, self-cleaning, self-healing, high ductility, and self-control of cracks. Concrete can be nano-engineered by the incorporation of nanosized building blocks or objects (e.g., nanoparticles and nanotubes) to control material behavior and add novel properties, or by the grafting of molecules onto cement particles, cement phases, aggregates, and additives (including nanosized additives) to provide surface functionality, which can be adjusted to promote specific interfacial interactions.”</p>

Figure 3.1 shows the particle size and specific surface area related to concrete materials.



Source: Sanchez and Sobolev, 2010 pp 2065

Figure 3.1 Particle Size and Specific Surface Area Related to Concrete Materials

The next section takes provides a chronological review of the literature (2001 through 2019).


In 2001, Nakamura and Meiarashi looked at NO_x removal using carbonized aggregate that was coated with TiO₂. They found that the NO_x removal capability was very high and could become a material for air pollution emission reduction (Nakamura and Meirashi, 2001). In their experiment they used a woody material (medium density fiberboard) of 15mm thickness that was processed to create globular woodchips. This was then coated with TiO₂ by soaking for five minutes; the fiberboard was then placed into a centrifuge to remove excess. This was then placed into a reactor vessel, and the composite was irradiated with UV rays using a black light, as test gas was introduced. NO_x concentration was measured for thirty minutes as the UV radiation finished. Using an electron microscope, the area coated with TiO₂ showed a change in surface area and the results showed that NO_x removal ratio was as high as 60%.

In 2008 Poon and Cheung looked at photocatalytic paving blocks (again coated with TiO₂ made from local waste materials—construction/demolition waste and waste glass cullet). These were then field trialed and monitored. They found that NO_x concentration was reduced approximately 13% at ground level and 10% at human height level (Poon and Cheung, 2007).

Guang et al., in 2008, developed a test chamber with 2, 3, 4, and 5% of nano TiO₂ photocatalytic materials that were mixed with high shear ultrasonic wave and dispersant to look at the degradation of NO_x, hydrocarbons (HC), and carbon monoxide (CO) from a tailpipe when vehicle was idle

(Guang, 2008). The test results were that “Nano titanium dioxide made by ultrasonic dispersant has the best degradation efficiency on NO_x of automotive emission. The nano titanium dioxide made by high shear, ultrasonic wave and ultrasonic dispersant, degrading of NO_x, HC, CO on automotive emission is 5%, 3%, 2%; 5%, 3%, 4%; 5%, 2%, 3% respectively” (Guang et al., 2008).

Bolte in 2009 looked at applications of the trademarked TioCem® used on roof tiles and cement blocks within a test chamber to measure exposure with and without light. This study found significant degradation of pollutants even at intensities “well-below those described in various measuring methods” (Figure 3.2).



4 Degradation rates as a function of initial NO content on concrete paving; air flow-rate 1 l/min.; UV-A intensity 2000 µW/cm²

Source: Bolte, 2009

Figure 3.2 Degradation Rates as a Function of NO Content on Concrete Paving

Sanchez and Sobolev in their 2010 review of nanotechnology in concrete noted that nano TiO₂ had been proven effective for self-cleaning of concrete, as well as the added benefit of reducing emissions, although there was some aging due to carbonation that could result in catalytic efficiency loss. Nano-SiO₂ [silicon dioxide] has also been found to improve concrete workability and strength and an increased resistance to water penetration, and had accelerated the hydration reactions of C₃S and ash-cement mortar and showed enhanced strength than silica fume. Many of these results were, however, highly dependent on the production route, conditions of the Nano-SiO₂ and the types of reagents and duration of the reaction in the sol-gel method. Nano-Fe₂O₃, they also noted, had been found to provide concrete with self-sensing capabilities as improved its compressive and flexural strengths (Sanchez and Sobolev, 2010).

Hassan et al. reviewed a nano-TiO₂ additive on asphalt binder aging properties in 2011. This study was undertaken as the technology was only being applied to concrete pavement surfaces, which represented about 6% of the national road network in the U.S. (Hassan et al., 2011). Asphalt, meanwhile, is used in approximately 94% of the U.S. road network (primarily hot-mix asphalt), and they thus considered that research was needed to developing a method for using TiO₂ coating in flexible pavements. They used a commercial crystallized anatase-based TiO₂ powder that was blended with a conventional asphalt binder (classified at PG64-16 at three modification rates 3%, 5% and 7% respectively). They found:

“Prepared blends were characterized with the use of fundamental rheological tests and with measurements of the environmental efficiency of the binder in removing part of the NO_x pollutants from the airstream. Results of the experimental program indicated that the use of TiO₂ as a modifier to asphalt binder was effective in removing part of the NO_x pollutants from the air stream. Rheological test results indicated that the addition of TiO₂ did not affect the physical properties of the conventional binder. Exposing the binder to ultraviolet light did not appear to accelerate the aging mechanisms in the binder” (Hassan et al., 2011).

Shen et al. studied the effectiveness of treated pervious concrete by comparing different TiO₂ application methods (Shen et al., 2012). At the time of testing they noted that there was very little commercial availability of photocatalytic building materials, and the average cost of ultrafine nano TiO₂ was \$9.07 per pound. They also tested the durability under freeze-thaw conditions with a de-icing agency and outside weathering. The batches of trial samples used six different TiO₂ coating methods and different concentrations in each.

1. **Cement/aggregate mix (CAM):** it was a thin layer of pervious concrete with finer aggregate size and TiO₂ mixed in. This could be used as a special application when surface maintenance is needed for pervious concrete.
2. **Driveway protector mix (DPM):** it consisted of a transparent liquid driveway protector and TiO₂ uniformly mixed together and brushed onto the surface of pervious concrete.
3. **Cement-water slurry high (CWSH):** it consisted of a relatively high concentration of cement and TiO₂ mixed into water and brushed onto the surface of pervious concrete.
4. **TiO₂ sprinkled on driveway protector (SDP):** it consisted of TiO₂ sprinkled onto driveway protector freshly painted on the surface of pervious concrete.
5. **TiO₂ sprinkled on fresh concrete (SFC):** it consisted of TiO₂ sprinkled onto fresh pervious concrete.
6. **TiO₂ mixed in water on fresh concrete (TIWF):** it consisted of TiO₂ sprinkled onto fresh pervious concrete (Shen et al., 2012)

Plain pervious concrete samples with no TiO₂ were also tested, as they were used as control specimens (Shen et al., 2012). Their analysis and testing found:

“High pollutant reductions were seen with a driveway protector mix, a commercial water-based TiO₂ preparation, TiO₂ in water, a cement-water slurry with low cement concentration, and the commercial PURETI coating. It was found that nitrogen oxide (NO) was efficiently removed with each of these treatments, while VOCs displayed more variability in removal efficiency. When pervious concrete was compared to traditional concrete, pervious concrete showed higher NO reductions. The PURETI coating had the lowest effect on reducing the infiltration rate of the pervious concrete. The driveway protector mix had the highest resistance against freeze-thaw testing with deicing chemical and environmental weathering. From Scanning Electron Microscopy (SEM), TiO₂ appeared to be more abundant and evenly distributed over the surface of the driveway

protector mix. Based on the findings from this study, it is recommended that each coating type be applied for different purposes. For example, the driveway protector mix would resist well in a highly abrasive environment, like on the shoulders of a highway or on busy sidewalks adjacent to a road. The transparent color of the commercial water-based TiO₂ could be used for aesthetic reasons. The cement aggregate mixes could be mixed into thin pervious concrete overlay, as a pavement maintenance technique. The PURETI treatment as a cost-effective alternative, where the surface abrasion is low. More studies need to be done to confirm each treatment's resistance against live traffic and against weathering during the colder and wetter seasons" (Shen et al., 2012).

At the American Society of Civil Engineers (ASCE) Transportation and Development Institute Congress in 2011, Schmitt et al. (Schmitt et al., 2011) presented "Impact of Mixed Nitrogen Dioxide (NO₂) and Nitrogen Oxide (NO) Gases on Titanium Dioxide Photodegradation of NO_x." This study evaluated the environmental effectiveness of TiO₂ coating in photodegrading mixed NO₂ and NO gases from the atmosphere. Their results indicated that *"Results of the experimental program determined that increasing the flow rate and NO₂/NO_x ratio negatively affect the effectiveness of the photocatalytic process. However, within the evaluated range, the titanium content and aggregate gradation had little impact on NO_x removal efficiency. The highest photo degradation rate was observed at 25% relative humidity, which balances the availability of hydroxyl radicals at the surface with NO_x contact with the photocatalytic surface"* (Schmitt et al., 2011).

Shen et al. (2012) also looked at the reduction of toluene, trimethylbenzene (TMB), and NO from automobile exhaust. Eight different application mixes were used.

"Commercial water-based TiO₂ (CWB): it consisted of Cristal Global's S5-300B commercial water-based TiO₂ brushed onto the surface of pervious concrete.

Cement-water slurry high (CWSH): it consisted of cement, water, and TiO₂ uniformly mixed together and brushed onto the surface of pervious concrete. The slurry was relatively thick compared to method

Cement-water slurry low (CWSL): it consisted of a thin slurry with low cement concentration and TiO₂ uniformly mixed together and brushed onto the surface of pervious concrete.

Driveway protector mix (DPM): it consisted of a transparent liquid driveway protector and TiO₂ uniformly mixed together and brushed onto the surface of pervious concrete.

TiO₂ in water (TIW): it consisted of water and TiO₂ uniformly mixed together and brushed onto the surface of pervious concrete.

PURETI (PUR): it consisted of the PURETI commercial water-based TiO₂ applied to the surface with a special electrostatic sprayer by the PURETI producer.

Cement/aggregate mix (CAM): it was a thin layer of pervious concrete with finer aggregate size and TiO_2 mixed in. This could be used as a special application when surface maintenance is needed for pervious concrete.

Cement/aggregate mix with higher TiO_2 concentration (CAMH): it was the same application method as method but with higher TiO_2 concentration.” (Shen et al., 2012)


Three control specimens were also tested. Plain pervious concrete with no TiO_2 (PPC), plain traditional concrete with no TiO_2 (PTC), and traditional concrete coated with the CWSH method (TCC). The results before abrasion are shown in Table 3.3. They also conducted tests for 0, 12- and 36-hour freeze thaw cycles as well. Results of toluene, TMB, and NO reduction can be seen in Figures 3.3 and 3.4.

Table 3.3 Summary of Results for Each Application Type Before Abrasion

Sample	TiO_2 (g/mm ²)	% of surface coating that is TiO_2	Static Chamber (120 min)		Flow- through Chamber (29.83 min) Total % NO reduction	NO decay rate, k (1/hr)	Converted Static Chamber (29.83 min) Total % NO reduction	% Decrease in infiltration rate
			total % toluene reduction	total % TMB reduction				
empty chamber	-	-	2.48%	12.35%	1.38%	0.09	4.61%	-
PPC	-	-	15.06±0.28%	29.86±8.83%	2.51±0.19%	0.17	8.31%	-
PTC	-	-	-	-	1.61%	0.111	5.37%	-
TCC	8.61*10 ⁻⁵	5.01%	-	-	13.95%	1.102	42.19%	-
CWB	5.27*10 ⁻⁴ (water-based TiO_2)	100% (water-based TiO_2)	61.86±14.06%	94.64±1.85%	52.46±2.07%	7.50	97.59%	20.60%
CWSH	8.61*10 ⁻⁵	5.01%	13.23±1.62%	81.65±1.50%	35.97±1.64%	3.82	85.04%	58.29%
CWSL	8.61*10 ⁻⁵	9.82%	78.82±9.22%	97.26±0.63%	50.79±0.49%	7.01	96.94%	51.50%
DPM	8.61*10 ⁻⁵	14.29%	61.65±10.77%	93.87±1.09%	53.27±3.63%	7.79	97.92%	30.49%
TIW	8.61*10 ⁻⁵	11.76%	91.98±3.08%	96.34±1.08%	51.30±2.43%	7.15	97.14%	-
PUR	2.02*10 ⁻⁶	-	43.42±1.79%	89.50±4.05%	48.29±3.13%	6.37	95.79%	11.92%
CAM	8.61*10 ⁻⁵	0.46%	21.62±4.30%	68.28±5.99%	19.11±3.46%	1.62	55.35%	3.85%
CAMH	2.17*10 ⁻⁴	1.15%	-	-	32.97±1.73%	3.34	81.03%	-3.49%


^a This data is not applicable or is unavailable.

Source: Shen et al., 2012



Source: Shen et al., 2012

Figure 3.3 Results for Static Chamber Reduction in Toluene and TMB after 120 Minutes



Source: Shen et al., 2012

Figure 3.4 Results for NO Reduction after 30 Minutes with Flow-through Chamber Data and Converted to Static Chamber Data

They also evaluated materials costs and effectiveness of pollutant reduction (Table 3.4). As the findings indicate, some coating types are more costly and the effectiveness needs to be considered in terms of durability, pollutant reduction, and initial costs.

Table 3.4 Material Cost & Observed In-Lab Pollutant Reduction for Each Coating Type

Coating type	MATERIAL COST		OBSERVED POLLUTANT REDUCTION			
	total material cost (\$/ft ²)	total material cost (\$/m ²)	Static Chamber (120 min)		Converted Static Chamber (29.83 min)	% Decrease in infiltration rate
			total % toluene reduction	total % TMB reduction	Total % NO reduction	
commercial water-based TiO ₂ (CWB)	0.9955	10.70	61.86±14.06%	94.64±1.85%	97.59%	20.60%
cement-water slurry (CWSH)	0.1860	2.00	13.23±1.62%	81.65±1.50%	85.04%	58.29%
driveway protector mix (DPM)	0.3876	4.17	61.65±10.77%	93.87±1.09%	97.92%	30.49%
Pureti (PUR)	0.1000	1.08	43.42±1.79%	89.50±4.05%	95.79%	11.92%
cement-water slurry low (CWSL)	0.1655	1.78	78.82±9.22%	97.26±0.63%	96.94%	51.50%
cement/aggregate mix (CAM)	0.3045	3.27	21.62±4.30%	68.28±5.99%	55.35%	3.85%
cement/aggregate mix high (CAMH)	0.3030	3.26	-	-	81.03%	-3.49%

4 - This data is unavailable

Source: Shen et al., 2012


They concluded by noting:

“Each coating type in this study could be useful for different purposes. For example, because the DPM maintained its high photocatalytic activity after exposure to deicing chemical and freeze-thaw cycles, this type of coating could be used in a highly abrasive environment, like on the shoulders of a highway or on busy sidewalks adjacent to a road. The CWB could be used for aesthetic reasons, where the white color of the DPM is not desired; the CWB is a transparent coating. The white color of the TiO₂ particles seen in the DPM coating could potentially be used as pavement marking materials, at the same time achieving air purification effect. The CAM and CAMH coating, TiO₂ mixed into thin pervious concrete overlay, could be used as a pavement maintenance technique to address minor surface raveling and cracking distresses at the same time produce photocatalytic

effect. The PUR is a cost-effective light coating, which is suitable for wide low traffic area where the surface abrasion is low.”

Meng et al. (Meng et al., 2012) looked at the effect of nano TiO_2 on the mechanical properties of cement mortar. In laboratory tests they conducted they when cement was substituted by nano TiO_2 they found that the strength of the cement mortar at early stages increased but decreased at later stages. They found that “*The compressive strength of cement mortar with 5% or 10% nano- TiO_2 at 1 day both increased by about 45%. But the compressive strength of cement mortar at 28 days decreased by 10% and 19% respectively and the fluidity decreased by 20% and 40% respectively when 5% and 10% cement was substituted by nano- TiO_2 .*” They also found that as a consequence of the high surface area of the nano TiO_2 they needed more water to enwrap the solid particle.

Pei et al. in 2012 (Pei et al., 2012) assessed the efficacy of using a prepared ferric ion (Fe^{3+}) modified TiO_2 to reduce emissions in tunnels. In their experiment they saw degradation rate in various catalysts doped with TiO_2 that were daubed onto a 300 x 300 mm glass sheet (Figure 3.5) and placed into an exhaust catalytic reaction equipment box they had made.



Source: Meng et al., 2012

Figure 3.5 Degradation rate of CO, CO₂, NO_x, HC under catalysis of TiO_2 doped with respectively 0.1%, 0.05%, 0.01% Fe^{3+} and unmodified TiO_2

They concluded that “*Doping Fe^{3+} improves photocatalysis performance of nanometer TiO_2 . The best catalytic effect could be obtained with a Fe^{3+} dosage of 0.1%, degradation rates of CO, CO₂, HC, NO_x are increased by 6.9%, 7.9%, 2.3%, 14.9% under ultraviolet light conditions; 0.6%, 0.6%, 2.3%, 8.2% under incandescent light conditions*” (Meng et al., 2012, pp 11).

Chen et al. in 2012 (Chen et al., 2012) reviewed the hydration and properties of nano TiO_2 blended cement composites. Two different types of nano TiO_2 particles were blended into cement pastes and mortars. They found the following:

“The addition of nano- TiO_2 powders significantly accelerated the hydration rate and promoted the hydration degree of the cementitious materials at early ages. It was demonstrated that TiO_2 was inert and stable during the cement hydration process. The total

porosity of the cement pastes decreased and the pore size distribution were also altered. The acceleration of hydration rate and the change of microstructure also affected the physical and mechanical properties of the cement-based materials. The initial and final setting time was shortened and more water was required to maintain a standard consistence due to the addition of thenano-TiO₂. The compressive strength of the mortar was enhanced, practically at early ages. It is concluded that the nano-TiO₂ acted as a catalyst in the cement hydration reactions” (Chen et al., 2012 pp 648).

Hassan et al. in 2012 (Hassan et al., 2012a) assessed the environmental performance of photocatalytic TiO₂ warm-mix asphalt pavements. They noted that the proper method for applying TiO₂ to asphalt pavements was unclear, and this study was to evaluate the benefits of incorporating TiO₂ in the preparation of warm mix asphalt. They used two types of application methods:


1. Water-based TiO₂ solution applied as a thin coating
2. TiO₂ added as a modifier to the asphalt binder

They found that the photocatalytic compound, when used as a modifier to the binder, was not effective in degrading NO_x in the air stream. This was attributed to the fact that only a small amount of TiO₂ was present at the surface. Conversely the thin coating solution surface spray *“was effective in removing nitrogen oxide (NO_x) pollutants from the air stream with an efficiency ranging from 31 to 55%.”* The coverage rate that achieved maximum NO_x removal efficiency was of 0.05 L/m². They noted, however, that *“durability of the surface spray coating requires further evaluation.”* They also found that the increase in flow rate of air (which included various pollutants) and relative humidity negatively impacted the efficiency and effectiveness of NO_x reduction efficiency. They also found that the increase in UV light intensity improved the NO_x removal efficiency of the surface coating (Hassan, 2012a).

In a different study in 2012, Hassan et al. (Hassan et al., 2012b) reviewed different types of methods to apply TiO₂ to concrete pavements. They reviewed three application methods.

1. Cement-based thin coating with a 10mm thickness
2. Water-based TiO₂ solution (PT) (2% TiO₂ suspended particles and a nano-size 95nm) photocatalytic grade, which gave coverage at a rate of 215 g/m²
3. Sprinkling nano sized TiO₂ particles on the fresh concrete surface before hardening. The particles were spread to a content of 3% and 5% after pouring.

The concrete sample dimensions were 305mm x 381mm x 25.4mm. The samples were then subjected to abrasion and wear using accelerated loading test and abrasion, and then the environmental efficiency of worn and original samples was measured using microscopic analysis. Figure 3.6 presents the results.



Source: Hassan et al., 2012b

Figure 3.6 NO Removal Efficiencies for Original, Worn, and Abraded Samples

They noted that in assessing for environmental effectiveness after wear and abrasion,

“it appears that the Load Wheel Tester slightly improved the NO removal efficiency of the different samples with the exception of samples with 5% TiO₂, which experienced a slight decrease in efficiency. This result may be due to the wear action simulated using the LWT, which exposed part of the embedded titanium dioxide particles at the surface and therefore improved the NO removal efficiency. In contrast, rotary abrasion appears to result in a decrease in NO removal efficiency for the 5% TiO₂ coating and the PT product while the efficiency slightly improved or remained constant for the other specimen types. In general, the samples coated with 5% TiO₂ and the PT product were the most efficient in removing nitrogen oxide from the air stream. The highest NO removal efficiencies in the original and RA states were measured for the coating with 5% TiO₂. On the other hand, the highest NO removal efficiency in the LWT state was measured for the samples treated with the PT product” (Hassan et al., 2012b pp 604).

Guerrini et al. in 2012 at the 10th International Conference on Concrete Pavements highlighted investigative projects conducted on photocatalytic roadway/tunnel coverings at three sites in the E.U.: in Bergamo, Italy, on a city road built of paving blocks; on a concrete city road in Paris, France; and a city road tunnel in Rome, Italy. All three in-situ experimental projects had been shown to have positive results (Guerrini et al., 2012).

Boonen and Beldens in 2012 reported on further E.U.-funded in-situ projects in Belgium, showing the differences from laboratory tests through to a pilot project in Antwerp. The on-site studies took measurements of air at 5 cm above the photocatalytic surface, and found that NO_x concentration did decrease (Boonen and Beldens, 2012).

In 2012 Churchill and Panesar looked at the life cycle cost analysis of highway noise barriers designed with photocatalytic cement (Churchill and Panesar, 2012). They found that:

“A key outcome from this study revealed that at a 40-year service life, assuming a 6 mg/h/m² NO_x degradation rate, a barrier designed with 100% General Use (GU) cement and a 25 mm photocatalytic concrete cover has an annual cost that is 7%, 30%, and 36% greater than the 100% GU, 35% and 50% Ground Granulated Blast Furnace Slag (GGBFS) barriers without a photocatalytic cover, respectively. Results of this analysis also indicated that the application of a 25 mm photocatalytic concrete cover to concrete containing 35 and 50% GGBFS is more economically feasible than 100% GU concrete, irrespective of the service life and pollution degradation rate” (Churchill and Panesar, 2012, pp 983).


They conducted a series of test and determined the annual cost of base case accounting for NO_x and PM₁₀ degradation, as Table 3.5 displays.

Table 3.5 Annual Cost of Base Case Accounting for NO_x and PM₁₀ Degradation

NO _x degradation (mg/h/m ²)	Service life (years)	Barrier design									
		D1	D2	D3	D4	D5	D6	D7	D8	D9	D10
6	20	400	328	313	555	425	367	355	400	406	413
6	30	348	285	272	481	369	318	308	347	352	358
6	40	327	268	256	452	347	299	290	326	332	337
6	50	319	261	250	440	338	291	282	318	323	328
20	20	400	328	313	538	417	359	347	392	398	404
20	30	348	285	272	464	361	310	299	339	344	350
20	40	327	268	256	436	339	291	281	318	323	329
20	50	319	261	250	423	330	283	273	309	314	319

Source: Churchill and Panesar, 2012 pp 990


They then reviewed the effect of GGBFS as a cement replacement and then the influence of NO_x degradation rate and P these results.



Notes: NO_x degradation rate: 5mg/h/m²

Source: Churchill and Panesar, 2012 pp 991

Figure 3.7 Effect of GGBFS as Cement Replacement and PCAT Concrete Cover on Annual Cost



Source: Churchill and Panesar, 2012 pp 991

Figure 3.8 Influence of NO_x Degradation Rate and PCAT Cover Thickness on Annual Cost

Their report states the following:

“The composite barrier designed with 100% GU cement and a 25 mm photocatalytic concrete cover has an annual cost that is 7, 30 and 36% greater than the 100% GU, 35% GGBFS and 50% GGBFS barriers without a photocatalytic cover, respectively at a service life of 40 years, and a 6 mg/h/m² NO_x degradation rate. For a degradation rate of 20mg/h/m², the annual cost of the barrier designed with 100% GU and a 25 mm PCAT concrete cover is greater than the 100% GU, 35% GGBFS, and 50% GGBFS barriers by 4, 27 and 33%, respectively. At all service lives, the noise barrier designs that add 25 mm photocatalytic concrete cover to a concrete base containing 35% and 50% GGBFS as cement replacement are more economically feasible than 100% GU concrete for both the 6 and 20 mg/h/m² NO_x degradation rates. For a service life of 40 years barriers with 35 and 50% GGBFS have annual costs that are respectively, 7.7% and 10.7% less than the design with 100% GU with a 6 mg/h/m² NO_x degradation rate and 10.3% and 13.3% less when the NO_x degradation rate is 20 mg/h/m². The noise barrier designs with the thinnest photocatalytic concrete covers, namely 5 mm (mix D8) and 10 mm (mix D9), are more economically feasible compared to barriers de-signed with 100% GU without photocatalytic cover (mix D1), for service lives which are 30 years or greater, modelled with a NO_x degradation rate of 20 mg/h/m². Combining thin covers with a base that contains GGBFS is the most economically feasible alternative. Increasing the pollution degradation rate from 6 to 20 mg/h/m² reduces the annual cost by approximately 2.4% irrespective of the photo-catalytic cover thickness. However, at a degradation rate of 20 mg/h/m² the barrier with a 10 mm photocatalytic cover thickness is more economically feasible than a 100% GU barrier without a photocatalytic cover when the cost of NO_x exceeds approximately \$9000/tonne” (Churchill and Panesar 2012, Pp 995).

They conclude by noting:

“The overall findings from this study indicate that photocatalytic cement has potential to be a socially, environmentally and economically feasible alternative for concrete noise barriers. It is however imperative to achieve high NO_x degradation rates for photocatalytic concrete barriers to become economically feasible. Selection of the orientation, geometry and exposed surface area of infrastructure containing photocatalytic cement should be carefully considered since the light intensity, relative humidity and wind characteristics influence the effectiveness of the photocatalytic processes...The influence of the degradation of particulate matter increases the annual cost savings through pollution reduction by 75%. Even though the pollution avoidance cost for particulate matter is quite high compared to other pollutants, the amount of particulate matter that can be degraded is still small due to the low, 19–300mg/m³, pollutant concentrations on primary road networks in Canada” (Churchill and Panesar 2012, Pp 995).

Hassan et al. in 2013 noted that field test of photocatalytic pavement technologies in the U.S. was still de minimus:


“to date, field evaluation of photocatalytic pavement technology has been limited. Hassan and co-workers laid the country’s first air-purifying photocatalytic asphalt and concrete pavements on December 20, 2010...on the Louisiana State University (LSU) campus: A customized distributor truck was used in the application of a TiO₂ water-based solution. Two parameters were necessary to remain constant during the application: speed and pressure. To maintain an accurate and steady speed of 50 foot per minute min, a magnet was placed on the drive shaft that counted each revolution. The distance covered per revolution was calibrated by counting the number of rotations, as the truck drove 100 feet.”

In this study Hassan et al. were looking at the sustainability of photocatalytic asphalt pavement for NO_x and SO₂ emission abatements. The field experiment looked at the direct measurement of NO_x reduction and the indirect measurement of NO_x reduction through nitrate analysis. Again, the researchers noted that the proper method to apply TiO₂ was unclear. Their results showed that TiO₂ was effective in removing NO_x in the laboratory at an efficiency range between 31 and 55%. TiO₂ was also effective in removing SO₂ pollutants, with a reduction efficiency of 19.8%. For the field test they noted that “*Results of the direct method and indirect methods of measuring photocatalytic degradation of NO_x show that there is evidence of a photocatalytic reaction occurring in the field*” (Hassan et al., 2013). This research as also reported out at the TRB 2013 annual meeting with David Osborn as lead author (Osborn, 2013).

In an indoor test conducted in Italy on Smart Tiles by Sannino et al. in 2013 (Sannino et al., 2013), the use of TiO₂ sprayed onto floor tiles in an indoor office environment was shown to completely remove NO_x from the air stream without deactivation of the TiO₂ film.

Asadi et al. (part of Marwa Hassan’s team at Louisiana State) in 2013 (Asadi et al., 2013) evaluated NO_x and NO removal efficiency with different void ratio and TiO₂ depths in pervious concrete in a series of laboratory experiments. Their results found that TiO₂ was effective in removing NO_x

pollutants with an efficiency ranging from 30% to 70%. The maximum amount of NO_x removal occurred at 3 inches depth of TiO₂ with a void ratio of 31% (Figure 3.9).



Source: Asadi et al., 2013

Figure 3.9 Effects of the Depth of TiO₂ and Void Ratio on NO_x Reduction Efficiency

Mohammed in 2014 reviewed the influence of nano materials on flexural behavior and compressive strength of concrete. He found that

“Mechanical properties have been investigated such as compressive and flexure strength through testing concrete prisms 40, 40 and 160 mm at 7, 28 and 90 days in order to explore the influence of these nanoparticles on the mechanical properties of concrete. Results of this study showed that nanoparticles can be very effective in improving mechanical properties of concrete, nano-silica (NS) is more effective than nano-clay (NC) in mechanical properties and wet mix gives higher efficiency than dry mix. Exceeding a certain percent-age of nanoparticles in concrete negatively affects the mechanical properties. Also, binary usage of nanoparticles; (NS + NC) had a remarkable improvement appearing in concrete compressive strength than using the same percentage of single type of nanoparticles. This improvement can be attributed to the reaction of nanomaterials with calcium hydroxide Ca(OH)₂ crystals, which are arrayed in the interfacial zone (ITZ) between hardened cement paste and aggregates, and produce C-S-H gel and the filling action of nanoparticles which cause more densified microstructure. A percent of 3% nanoparticles consisting of 25% NS and 75% NC gave the highest mechanical properties representing in both compressive and flexure strengths among other percentages (Mohamed, 2014, pp 212).

In 2014 Dylla et al. (Dylla et al., 2014) (part of Marwa Hassan’s team) moved to look at the reduction of nitrogen monoxide through degradation using TiO₂ nanoparticles. In this study they developed an environmental model to assess the photocatalytic reaction kinetics of NO reduction under varying environmental conditions. Again they noted that the current understanding of photocatalytic pavements in real world settings was lacking. In reviewing the chemical properties they noted that the reaction scheme that irradiation and the absorbed reactants (water, O₂, and NO) all play a role in the PCO. They set up a photoreactor in their lab and used a typical meteorological

year to determine their environmental parameters. They found that the “NO reduction per initial concentration at 51% relative humidity and 2.1 mW/cm² light intensity. As the concentration increases, the percentage of NO degradation decreases, which was the trend for all the tested run scenarios” (Dylla et al., 2014). They concluded that further research was needed to develop a NO reaction rate model for photocatalytic pavements to understand real-world environments and reactions because:

“The results of the parametric study identified that the relative humidity and light intensity both had a significant impact on the L-H constants and there was an interaction effect between the relative humidity and light intensity. The impact of the relative humidity played a significant role on the L-H equilibrium constant, K_d. Contrary to theory, as the humidity increased, the K_d increased, suggesting that additional phenomena to the typical competition of adsorption sites between water and the pollutant play a role in the K_d adsorption, including NO diffusion and dissolution in water. Irradiance significantly affects the reaction rate, k. With higher irradiance, more energy creates more active sites” (Dylla et al., 2014).

In 2014 members of this same team (Osborn et al., 2014) produced papers for TRB and ASCE’s *Journal of Materials in Civil Engineering* on the durability quantification of TiO₂ surface coating on asphalt and concrete pavements. They found that their results suggested that the durability of a TiO₂ treated photocatalytic pavement resulted in a service life for a concrete pavement between 6 and 11 months and for an asphalt pavement between 10 and 16 months (Osborn et al., 2014).

In 2015 Nadiri, Hassan, and Asadi began work on developing a model, based on field data they collected, to predict the NO_x reduction from using a TiO₂ nanoparticle pavement coating (Nadiri et al., 2015). A “*supervised intelligent committee machine (SICM) method as a combinational black box model was used to predict NO_x concentration at the pavement level before and after TiO₂ application on the pavement surface.*” They used three AI models—Mamdani fuzzy logic, artificial neural network, and neuro-fuzzy—to predict NO_x concentration in the air as a function of traffic count and climatic conditions (temperature, humidity, solar radiation, and wind speed) before and after TiO₂ was applied. Their results indicated that the SICM model could provide a reasonable better prediction of NO_x concentration as an air pollutant (the model had less mean square error than using multivariate regression models) (Nadiri et al., 2015).

Verbruggen in 2015 (Verbruggen, 2015) looked at TiO₂ photocatalysis for the degradation of pollutants in the gas phase. In looking at porous and interconnected and supported structures, he noted that:

“Although quite some benefits are associated with the use of nanoparticles, a big disadvantage is that they have high tendency to agglomerate into larger aggregates. Generally this is at the expense of photocatalytic activity, but in particular cases it can also lead to an improved efficiency. Bahnemann’s group have proposed the ‘antenna mechanism’, which involves the transfer of photon energy from one nanoparticle to another when they are arranged as an interconnected network along a fixed crystallographic

orientation. This could be an important effect in many TiO_2 powders consisting of large secondary agglomerates of closely interconnected crystalline nanoparticles. In many other cases, however, TiO_2 nanoparticles are incorporated into (porous) substrates or alternatively, (ordered) interconnected 3D structures of pure TiO_2 are synthesized” (Verbruggen, 2015 pp 70).

Verbruggen concludes his review by noting that

“From a socio-economic perspective, photocatalytic air purification still offers great opportunities. Already 15 years ago, Fisk estimated that the productivity gains that may be obtained by improving indoor air quality in the United States amount to 6–14 billion USD by reducing respiratory diseases, 1–4 billion USD by reducing allergies and asthma, 10–30 billion USD from decreased Sick Building Syndrome (SBS) symptoms and 20–160 billion USD dollars by improving general worker performance. In that regard it is surprising that a BCC Research market survey from 2010 reported that only 0.5% of the total photocatalyst product sector is directly related to environmental applications. The largest share (87.4%) is accounted for by the construction sector (photocatalysts in building materials). It has to be noted that the latter can also indirectly exert a beneficial influence on the environment, mainly through passive systems (e.g. coated surfaces exposed to the surrounding environment). Given these appealing prospects and the ample room for growth in the photocatalyst sector for environmental applications, it is wise not only to focus on improving the performance of photocatalysts through all kinds of high-end modification methods, but also keep taking into account the resulting costs, especially with the eye on commercialization.”

Macphee and Folli in 2016 looked at photocatalytic concretes and the interface between photocatalysis and cement chemistry. Their research addressed “(i) the photocatalytic mechanisms applicable to atmospheric depollution, (ii) the influence of doping, and (iii) the application of TiO_2 -based photocatalysts to concrete. Modifications to TiO_2 will be discussed which can improve its activation in visible light and, in the treatment of NO_x , improve catalytic selectivity towards nitrate rather than the more toxic NO_2 .” Their findings looked at a number of key physico-chemical factors, among others, and noted that:

“Pollutant degradation must be viable based on oxidation potentials relative to semiconductor band edge positions—these are pH dependent.

Geographical limitations of photocatalytic concrete will not be over-come by conventional TiO_2 —more fundamental research is needed to optimize the photonic efficiencies of visible light photocatalysts.

Catalyst surface area must be maximized for the target application; care must be taken to ensure particle dispersion is optimized. Agglomeration can block access to internal surface, i.e. if pollutant molecule size is greater than pore entry diameter.

Conventional TiO_2 is often very unselective and exhibits large negative DeNO_x index, a sign of ineffective catalytic process (too much NO_2 is released). Increasingly photocatalyst

selectivity, not only activity, is required to reduce emission of harmful by-products” (Macphee and Folli, 2016 Pp 54).

Nayak et al. in 2016 (Nayak et al., 2016) reviewed the effects of surface carbon on the visible-light photocatalytic activity of nitrogen doped TiO₂-C nanocomposite powder. In his method he used nitrogen doped TiO₂-C composite nanoparticles and the powder and structures were analyzed by X-ray photoelectron spectroscopy, and X-ray diffraction and transmission electron microscopy and optical properties was studied by UV-visible light absorption. The visible photocatalytic activity of black TiO₂ powder was investigated by studying the photobleaching of methylene blue under solar irradiation. The effect of surface concentration of the carbon and nitrogen on the visible photocatalytic efficiency of the black-TiO₂ was assessed. White TiO₂ powder without surface carbon was also synthesized and compared with that of the black TiO₂ powder. Nayak et al. found that:

Black TiO₂ was purely anatase whereas white TiO₂ had mixed phase character with 68% anatase and 32% rutile. Compared to white TiO₂, black TiO₂ could absorb more visible light. Unlike white TiO₂, Black TiO₂ is an efficient solar photocatalyst responsible for the photodegradation of 52 µM aqueous solution of MB with a first order rate constant, $k = 0.02 \text{ min}^{-1}$. The photocatalytic activity of black-TiO₂ strongly depended on the surface carbon concentration. The photo-catalytic activity of black-TiO₂ increases with increased carbon content. When the surface concentration exceeded 28%, the catalytic activity decreased presumably due to slower rate of charge transfer onto the TiO₂ nanoparticle surface. No such systematic change in the photocatalytic activity of black-TiO₂ was observed with change in its N content.

In 2017 Singh et al. undertook a review of the nanoscience of cement and concrete. They concluded “currently, the most active research areas dealing with cement and concrete are: understanding of the hydration of cement particles and the use of nano-size ingredients. Concrete science is a multidisciplinary area of research where nanotechnology potentially offers the opportunity to enhance the understanding of concrete behavior, to engineer its properties and to lower production and ecological cost of construction materials” (Singh et al., 2017 pp 5486).

Research is also currently looking at sensor capacity and nanotechnology. For example, Tang et al. in 2017 looked at a formaldehyde sensor based on a molecularly imprinted polymer on a TiO₂ nanotube array (Tang et al., 2017).

Faraldos and Bahamonde in 2017 in *Catalysis Today* began to look at the use of titania graphene photocatalysts. They began by noting that:

“Recently, graphene is receiving great attention in the area of photocatalysis...and emerging in the next generation of photocatalysts, as a tool for enhancing photocatalytic performance and solar photo efficiency. Titanium dioxide hybridization with graphene has an effect on band gap energy decrease, shifting its absorption threshold to the visible light region and allowing it to harness solar energy. So, the conjugation of graphene with

semiconductor solid particles such as TiO_2 , results in photocatalysts with improved charge separation, reduced recombination of the photo generated electron-hole pairs, increased specific surface area, and introduces an adequate quantity and quality of adsorption sites, given that enhances their electronic, optoelectronic, electrocatalytic and photocatalytic properties.”

In their review of the literature they noted that there were few papers on TiO_2 graphene composites for air pollution, and few looking at their use in photocatalytic waste water applications. The use of nanotechnology for reduction of waste water pollutants may be a further area that TxDOT may want to review. They conclude by noting that *“It is necessary to widen the scope where photocatalytic applications of graphene oxide-titanium dioxide composites could be useful: different pollutants, real water effluents, self-cleaning materials, biocide coatings, etc. are fields that still need to be explored”* (Faraldos and Bahamonde, 2017 pp 27).

Norhasri et al. in 2017 conducted another review of applications of using nano material in concrete (Norhasri et al., 2017). They reviewed nano silica, nano alumina, carbon nanotube, polycarboxylates, titanium oxide nano kaolin, and nano clay and found that the addition of ultrafine nano materials aided in formation of micro pores and acted as a filler agent to produce a denser concrete.

Reches in 2018 also reviewed nanoparticles as concrete additives (Reches, 2018). He found that “Nanoparticles are highly efficient additives for modification of cement products, even at small concentrations ($\leq 1\%$). The main modifications are (typical ranges shown, though great variability has been observed): reduction of set time (by 1–2 h) and diffusivity (by 4–75%), and increase of strength (by 5–25%), and thermal durability (0–30% increase in residual strength)” (Reches, 2018). These modifications were attributed to the unique reactivity of nanoparticles associated with their small size and large surface area. The paper reviewed SiO_2 , Al_2O_3 [aluminum oxide], Fe_2O_3 [ferric oxide], TiO_2 , CaCO_3 [calcium carbonate], and clay nanoparticles, and assessed effective modification mechanisms and potential commercial application challenges, including cost and dispersion. He concluded that further that

“Optimization of technologies and protocols for dispersing NPs, and for characterizing their dispersion state in situ in the cement products. The use of nano-powders does not apparently accommodate good dispersion; and while sonication with or without dispersing agents improves dispersion, NPs remain in large agglomerates. It seems crucial that cement researchers will need to become involved in the synthesis of NPs designed with their needs in mind, including particularly the application of a ligand to maintain mono-particle-dispersion, while taking care that any ligand does not hamper the functions of the NPs, OPC, or admixtures” (Reches, 2018, pp 493).

A field study survey of the NO_x removal efficiency of catalytic in a Korean expressway was reviewed in 2018 by Kim et al. (Kim et al., 2018). In this test experiment on a real-world road, Kim et al. used surface penetration agents to add TiO_2 to the surface of the concrete structure. The

study evaluated the in-situ NO_x removal efficiency of the TiO₂ penetration method on the retaining wall of the Gyeongbu expressway in Korea. The results indicated that the quantity of sunlight influenced the NO_x removal efficiency rate. The research team determined that the TiO₂ penetration method can be an alternative to using existing TiO₂ concrete. The results found that after the penetration method of applying TiO₂ took place, the NO_x concentration removal rate was approximately 0.07 ppm, or about 13% efficiency in removing the pollutant. The TiO₂ penetration method, applied as a mixture of TiO₂ and surface penetration agents at 500 g/m², was determined to be a feasible alternative method for removing the NO_x gases in areas with a high volume of traffic (Kim et al., 2018).

Leng et al. in 2018 reviewed the air-purifying performance of asphalt mixtures coated with TiO₂. They custom-designed an environmental test setup to determine the NO_x degradation efficiency of their specimens with TiO₂ coating, and the durabilities of the coating materials were characterized by measuring their NO_x degradation efficiency subjected to different numbers of lab-simulated tire abrasion (Leng et al., 2018). They used three coating methods (Table 3.6) and preparation processes and had one control group (Table 3.7). Figures 3.10 and 3.11 present the results.

Table 3.6 Preparation of Three Coating Solutions

Coating method	Materials	Preparation process
WT	Water and TiO ₂	Mixing TiO ₂ particles directly with water by magnetic stirring for 40 min
PT	Tetrahydrofuran (THF), polystyrene (PS), asphalt binder, and TiO ₂	Mixing asphalt binder, THF, PS, and TiO ₂ together by ultrasonic dispersion and magnetic stirring for 40 min and 2 h, respectively
GT	Glass bead, coupling agent, ethyl alcohol and TiO ₂	Mixing TiO ₂ and coupling agent KH570 and enough amount of alcohol at 60 °C, followed by ultrasonic dispersion for 1 h


Source Leng et al., 2018, pp 4

Table 3.7 Test Groups

Marshall specimens with different coating solutions.

Group ID	TiO ₂ content on each sample	Number of samples
CG (control group)	0 g	3
WTM (mixture with water-based TiO ₂ coating)	0.4 g	3
L-PTM (mixture with low rate porous TiO ₂ coating)	0.1 g	3
H-PTM (mixture with high rate porous TiO ₂ coating)	0.4 g	3
L-GTM (mixture with low-rate glass-bead-based TiO ₂ coating)	0.1 g	3
H-GTM (mixture with high-rate glass-bead-based TiO ₂ coating)	0.4 g	3


Source Leng et al., 2018, pp 4



Source Leng et al., 2018

Figure 3.10 NO Removal Efficiency Results

They found that “both the two novel coating methods, PT and GT, provide better NO_x removal efficiency than the conventional WB coating method. The GT method provides the coating material the best abrasion resistance, followed by the PT method and WB method. Considering the removal efficiency and durability, GT is the most promising coating method to incorporate nano-TiO₂ particles onto asphalt pavement” (Leng et al., 2018).



Source: Leng et al., 2018


Figure 3.11 Durability Results

Luevano-Hipolito and Martinez-de la Cruz in 2018 reviewed the use of TiO₂ in stucco for NO_x removal by real weatherism (Luevano-Hipolito and Martinez-de la Cruz, 2018). They created an artificial weathering chamber and aged the stucco over 14 days. The test blocks were then placed

into a chamber and removed every 100 hours with total exposure time set at 1000 hours. They noted that:

“the formation of CaCO_3 by carbonation reaction gradually blocks the porosity of the coating, which impacts negatively the specific surface area property. The biggest decrease in the surface area value took place during the first 100 hours of treatment. However, the decrease in the value of surface area seems not affect significantly the photocatalytic activity of CleaNO_x . In this regard, the CaCO_3 forming by the carbonation reaction can help to maintain the activity by promoting the absorption of NO_x gases in the coating surface. In this context, it has been reported the use of CaCO_3 as absorber of gaseous pollutants such as NO_x and SO_x in flue gas.” (Luevano-Hipolito and Martinez-de la Cruz 2018, pp 306

After these initial findings they then aged their samples in the open air for a year. Figure 3.12 shows the NO_x conversion over the months.



Notes: P-25 Exposed at Weathering Conditions During Year 1 ($Q = 1 \text{ L min}^{-1}$, $I = 10.1 \text{ W m}^{-2}$, $\text{RH} = 70\%$)

Source: Luevano-Hipolito and Martinez-de la Cruz 2018, pp 308

Figure 3.12 NO Conversion Degree Using Photocatalytic Coating with TiO_2

They concluded that:

“The development of the construction material CleaNO_x with photo-oxidative active surface for removal of NO by the action of solar radiation is proposed. In addition, the photocatalytic coating has the ability to capture CO_2 from air by means of a carbonation process. The active material $\text{TiO}_2\text{SG7}$ synthesized was a result of an optimization of the synthesis method in order to have a photocatalyst with an efficient NO conversion degree. The results indicated that the introduction of the active oxide in the inorganic matrix has a dilution effect on the photocatalytic activity, however its photocatalytic activity was retained after the incorporation in the matrix. The exposure of the coating to weathering conditions promoted the carbonation of the surface, which product tends to block the active

sites and decrease the photocatalytic activity by a poisoned effect. Also, the coating can storage dust or material particulate from the environment, which had a detrimental effect in the photocatalytic activity. This poisoning can be removed by a washing process, and after that, the surface coating maintained almost its original photocatalytic activity. In addition, when the coating was exposed under weathering conditions for 1 year, the results show that it requires a humid environment with relative low temperatures to promote an efficient removal of NO and CO₂ gases” (Luevano-Hipolito and Martinez-de la Cruz 2018, pp 308).


Papoulis, in 2019, looked at halloysites-based nanocomposites and photocatalysis as a promising area for review and to improve on a known adverse catalytic impact seen in TiO₂: agglomeration into larger particles over time (Papoulis, 2019). Halloysite nanotubes are found in natural clay, and can facilitate modification and growth of other functional materials for PCO. While halloysite is not a photocatalyst in itself, in combination with other photocatalysts or if it is used as a substrate, it improves the PCO of the end material. This is due to the high BET surface area, whereby high absorptivity heightens interaction with a nano-product and promotes the photocatalytic properties. In the Papoulis review of photocatalytic decomposition of inorganic air pollutants, volatile organic compounds (VOCs), Azo dyes, and photocatalytic decomposition of antibiotics/drug components/pesticides the study assessed the use of halloysite TiO₂ nanocomposites in various papers. All the papers and tests were found to have promise. However, Papoulis noted that only NO_x decomposition had been measured with some modification of halloysite with another technique and the paper suggested further research was needed to test.

3.2.1. U.S. Patent Applications

The literature review search discovered a few patent applications for nanotechnology and highway use. The most relevant is U.S Patent application 2005/0159309 A 1, July 2005 by Hubbell et al., which envisioned:

“A highway Safety equipment System using Solid catalyst crystal, Such as titanium dioxide, targeted for the breakdown of fluid borne undesirable material, Such as "Smog utilizing Standard, commonly encountered, U.S. Federal Highway Administration (FHWA), National Cooperation Highway Research Program (NCHRP), and/or American Association of State Highway and Transportation Officials (AASHTO) Standard Specification items. Such as highway guiderail, highway signing, highway Signal equipment, housings, toll booth, bridgework, bridge rails and/or Such items Support Structures...the present invention utilizes the teachings of U.S. Pat. No. 6,676,279 (279) and U.S. Pat. No. 6,705,744 (744) to Hubbell, et al. (a co-inventor of the present invention). Patents 279 and 744 teach that prior art systems for illuminating large, distant areas generally are deficient in that they produce light pollution, confusing night time driving conditions, light trespass, glare, energy waste, high maintenance cost and contribution to urban sky glow. The present invention is directed to a need to provide an area lighting and/or other wavelength radiation device that avoids the shortcomings of the prior art lighting Systems.”

A search of the U.S. Patent Office database does not show this patent as being approved. Figure 3.13 provides the drawings included in the application.



Source: U.S. Patent and Trade Mark Office
Figure 3.13 United States Patent Application

3.2.2. The Hype Around Nanotechnology and Emission Reduction

The literature review also revealed that as in many disruptive type technologies, there is much hype surrounding the ability of nanotechnology to achieve its potential goals. There is also growing concern that the use of nanotechnology will have unintended consequences. The literature review revealed that much of the research conducted to date has been in a laboratory setting, is expensive, and has focused upon a singular product in the transportation setting. Making the jump out of the Valley of Death into the Middle Ground (to use the GAO's terms) has yet to be achieved. In the context of the concrete industry—which provides immense quantities of product at globally set prices in an industry that some might call “old fashioned”—emission-reduction nanotechnology's ability to find a home will require reliable and cost-efficient products that are replicable in any geoclimate and for any type of mode. Raki et al. (Raki et al., 2010) noted that:

“the nature of the construction industry is such that it is easier to implement process innovations, rather than disruptive product innovations. Construction integrates products from a wide range of suppliers and skills from a wide range of contractors, subcontractors and trades into a single finished structure. A change in the way a structure is built can be determined by the construction company itself, but a significantly new product needs to be created by a supplier, understood and approved by architects, engineers and the client and implemented by on-site workers who may need to be specifically trained in its use.

All of these factors must be taken into consideration in developing nanotechnology for use in concrete. First, concrete and related products are bulk commodities. Even high value concrete structures require low materials costs and the ability to handle large quantities of material in a safe and environmentally acceptable manner. Second, innovations need to be thoroughly developed and field tested in order to build the knowledge and confidence in

the construction community. Finally, concrete structures can be difficult to demolish, often requiring explosive or other high-energy approaches as an initial step to break up the major components of the structure. Nanotechnology used in concrete must therefore be compatible to these traditional practices.

Given these constraints, the initial nanotechnology applications in construction are those that provide a clear benefit in terms of added functionality with relatively small amounts of nanomaterials that can be delivered in using standard construction practices and will not affect other aspects of the performance of the material. Novel products that improve the delivery of existing materials, such as the control released admixture work described here, are likely to be next to market. Other innovations, such as nano calcium carbonate accelerators, will become more common as the price of the nanomaterial falls to the point where it can be used in bulk. Carbon nanotube/cement composites, in contrast, will likely take the longest time to implement as they will require further fundamental research, reductions in CNT [carbon nanotube] prices, the development of specialized delivery techniques and equipment, greater understanding of the environmental impact of CNTs and specialized demolition methods before wide spread adoption can occur.”

Raki et al. also noted that “A key factor to economic viability is the need for the cost of the nanoparticles to be lower than the cost of the cement that is replaced. This condition in turn implies that much lower nanoparticle contents should be used in the blend than the percentage of cement that was replaced. Providing this condition is met, significant economic benefits are possible through reduction of the amount of cement used in a structure” (Raki et al., 2010).

Concerns are also being raised on the toxicology of nano technology—what could be called the *unintended consequences*. The CRS and GAO have noted that further studies are needed in this area. Schmid et al., in a 2009 article in *Biomarkers*, looked at dosimetry and toxicology of ultrafine particles (<100nm) on the brains, lungs, and major pathways. They found that “BET surface area is emerging as the single most relevant dose parameter for particle toxicity both in the ultrafine (<100 nm) and fine (100–2500 nm) size range” (Schmid et al., 2009).

The GAO noted in its May 2010 report (GAO, 10-549, 2010) that:

“The extent to which nanomaterials present a risk to human health and the environment depends on a combination of the toxicity of specific nanomaterials and the route and level of exposure to these materials. Although the body of research related to nanomaterials is growing, the current understanding of the risks posed by these materials is limited. This is because the manner in which some studies have been conducted does not allow for valid comparisons with newer studies or because there has been a greater focus on certain nanomaterials and not others. Moreover, the ability to conduct necessary research on the toxicity and risks of nanomaterials may be further hampered by the lack of tools to conduct such studies and the lack of models to predict the characteristics of nanomaterials.

EPA has undertaken a multipronged approach to understanding and regulating the risks of nanomaterials, including conducting research and implementing a voluntary data collection

program. Furthermore, under its existing statutory framework, EPA has regulated some nanomaterials but not others. Although EPA is planning to issue additional regulations later this year, these changes have not yet gone into effect and products may be entering the market without EPA review of all available information on their potential risk. Moreover, EPA faces challenges in effectively regulating nanomaterials that may be released in air, water, and waste because it lacks the technology to monitor and characterize these materials or the statutes include volume based regulatory thresholds that may be too high for effectively regulating the production and disposal of nanomaterials” (GAO, 10-549, 2010 pp 2).

The GAO in its 2014 report *Nanomanufacturing Emergence and Implications for U.S. Competitiveness, the Environment, and Human Health* noted that:

“Forum participants offered a wide range of perspectives on the environmental, health, and safety (EHS) implications of nanotechnology, nanomanufacturing, and nanomaterials. Forum participants presented information on what is currently known about these implications and expressed frustration about the lack of progress in understanding the risks from potential exposure to nanomaterials. Participants specifically noted a current dilemma related to identifying or determining EHS risks. Because so few nanomaterials have been studied and no long-term or chronic data are available, it is very difficult to predict and manage risks for new nanomaterials. Forum participants also identified significant research needs to discern EHS implications, and they discussed the need to fully communicate the benefits and risks of nanotechnology to the public, helping to distinguish between perceived and real risks” (GAO 14-181SP, 2014 Pp 55).

There is some hype around photocatalytic surface’s ability to reduce emissions, and concerns about potential side effects. The UK’s Department for Environment, Food and Rural Affairs in 2016 noted that:

“Taken as a whole, there is little current evidence to suggest the widespread use of photocatalytic surfaces will reduce ambient concentrations of NO₂. Furthermore, there is a risk that these materials will result in the production of other undesirable species such as nitrous acid and formaldehyde, which can have wider impacts on atmospheric chemistry as well as adverse health impacts. Photocatalytic surfaces can reduce concentrations close to the treated surface but this will not result in significant reductions in NO₂ concentrations in the surrounding air. It is not physically possible for large enough volumes of air to interact with the surface under normal atmospheric conditions and therefore this method will not remove sufficient molecules of NO₂ to have a significant impact on ambient concentrations” (DEFRA, 2016).

Crispino et al. in 2010 evaluated the long term environmental and functional performances of innovative photocatalytic road pavements. They found in their experiments that:

Data collected from the experiments carried out showed that photocatalytic road materials induced a significant reduction in air pollutants concentration (NO_x reduction up to 40%

were found). Moreover, TiO₂ durability was investigated, evaluating the resistance of the photocatalytic emulsion to wearing through the Wheel Tracking Test. The purpose of these tests was to simulate field conditions and long term performances of photocatalytic road pavements, to measure the ability of sprayed bituminous pavements to reduce NO_x during the whole life of the wearing course. *Results showed that increasing load cycles, photocatalytic activity of sprayed material is reduced up to half of the initial value.* Such result also demonstrates the wearing effect from Wheel Tracking Test on sprayed photocatalytic emulsion but the correlation between wearing effects from such device and real traffic is still to be found. Further research is therefore strongly recommended to investigate long term performances of photocatalytic road pavements also in term of economical vantages for the environment.”

Hassan, in a 2009 study on the evaluation of the environmental impacts of TiO₂ photocatalyst coatings for pavements using life-cycle assessment, also found that

“Life Cycle inventory (LCI) for titanium dioxide coating considers energy and emissions associated with the manufacturing of titanium dioxide, production of aggregate, plant operations, cement and surface mix production, and titanium dioxide coating placement (including transportation to the site and site worker transport). However, the developed LCI *does not consider* energy, materials, and emissions associated with the production or construction of the supporting concrete pavement. In addition, it does not consider energy associated with the production of fuels known as pre combustion, or energy associated with manufacturing of equipment needed to produce titanium dioxide.”

Hassan noted that “emissions associated with background processes including production of fuels and equipment were quantified using Input-Output life cycle assessment” (Hassan, 2009).

There has been concern about the trade-offs for nanotechnology and photodegradation intermediates and end products in terms of their impacts on air and water.

Dylla and Hassan in 2013 studied whether nanoparticles and nitrates released to water from photocatalytic pavements were shown to have adverse effects. Here Dylla and Hassan evaluated and measured the amount of TiO₂ nanoparticles and nitrates released to water from photocatalytic concrete pavements. Measurement of the amount of nitrates eluted to water was measured after 4.5 hours of PCO of NO_x where the settings were set to induce a high amount of NO_x reduced and nitrates created. They found:

After 4.5 hours of photocatalytic activity, 8.984 μmols of nitrates were released to water accounting for 49% of the theoretical amount of nitrates created. In addition, the amount of the titanium element was measured using inductive coupled plasma atomic emission spectrometry (ICP-AES). Titanium nanoparticles were not detected in any of the water samples (Dylla and Hasan, 2013).

References

- Biello, David. December 18, 2008. *Government Fails to Assess Potential Dangers of Nanotechnology*. Scientific American. URL <https://www.scientificamerican.com/article/government-fails-to-assess-dangers-of-nanotechnology/>
- Bolte, Gerd. (2009). Innovative Building Material - Reduction of Air Pollution through TioCem (R). 10.1007/978-3-642-00980-8_6.
- Congressional Research Service (CRS). December 16, 2014. *The National Nanotechnology Initiative: overview, Reauthorization and Appropriation Issues*. (Authored by John F. Sargent Jr). URL <https://fas.org/sgp/crs/misc/RL34401.pdf>
- CRS. September 15, 2016. *Nanotechnology: A Policy Primer*. URL <https://fas.org/sgp/crs/misc/RL34511.pdf>
- Cuffari, Benedette. *Nanotechnology in the U.S.A: Market Report*. AzoNano Magazine. URL <https://www.azonano.com/article.aspx?ArticleID=4973>
- European Commission. 2013. *Nanotechnology: The Invisible Giant Tackling Europe's Future Challenges*. URL https://ec.europa.eu/research/industrial_technologies/pdf/nanotechnology_en.pdf
- Fletcher, Harriett. September 4, 2017. *Smog Eating Paint Does More Harm Than Good*. Chemistry World. URL <https://www.chemistryworld.com/news/smog-eating-paint-does-more-harm-than-good/3007932.article>
- Guitierrez, Eva. Not dated. *Privacy Implications of Nanotechnology*. An Essay for the Electronic Privacy Information Center. URL <https://epic.org/privacy/nano/>
- Hassan, Marwa; Louay N. Mohammad, Samuel B. Cooper III, and Heather Dylla (2011) Evaluation of Nano-Titanium Dioxide Additive on Asphalt Binder Aging Properties. Transportation Research Record: Journal of the Transportation Research Board, No. 2207, Transportation Research Board of the National Academies, Washington, D.C., 2011, pp. 11–15.
- Hassan, Marwa; Heather Dylla, Somayeh Ashadi, Louay N. Mohammad, and Samuel Cooper (2012a) Laboratory Evaluation of Environmental Performance of Photocatalytic Titanium Dioxide Warm-Mix Asphalt Pavements. *Journal of Materials in Civ. Eng.*, 2012, 24(5): 599-605. [http://dx.doi.org/10.1061/\(ASCE\)MT.1943-5533.0000408](http://dx.doi.org/10.1061/(ASCE)MT.1943-5533.0000408).
- Hassan, Marwa; Heather Dylla, Louay N. Mohammad, and Tyson Rupnow (2012b) Methods for the Application of Titanium Dioxide Coatings to Concrete Pavement. *International Journal of Pavement Research and Technology*. 5(1):12-20.
- Leng, Zhen & Yu, Huayang & Gao, Zheming. (2018). Study on air-purifying performance of asphalt mixture specimens coated with titanium dioxide using different methods. *International Journal of Pavement Research and Technology*. 10.1016/j.ijprt.2018.08.003.

- Klein Leichman, Abigal. January 16, 2018. *New Paint Transforms Sun's Rays into Cool Air-Conditioning*. Israel 21c. URL <https://www.israel21c.org/new-paint-transforms-suns-rays-into-cool-air-conditioning/>
- Mihail C. Roco, Chad A. Mirkin, and Mark C. Hersam, eds., *Nanotechnology Research Directions for Societal Needs in 2020* (Netherlands: Springer, 2010).
- Nanotechnology in Construction 3 (2009). Z. Bittnar, P.J.M. Bartos, J. Nemecek, V. Smilauer, J. Zemen, eds. Proceedings of the NICOM3. DOI 10.1007/978-3-642-00980-8
- National Academies Research Council. 2002. *Small Wonders Endless Frontiers: A Review of the National Nanotechnology Initiative 2002*. URL <https://www.nap.edu/catalog/10395/small-wonders-endless-frontiers-a-review-of-the-national-nanotechnology>
- National Nanotechnology Initiative. *Nanotechnology and the Environment. Report of the National Nanotechnology Initiatives Workshop*. May 8-9, 2003. URL https://www.nano.gov/sites/default/files/pub_resource/nanotechnology_and_the_environment_app_imp.pdf
- National Science and Technology Council. August 2018. *The National Nanotechnology Initiative Supplement to the President's 2019 Budget*. URL <https://www.whitehouse.gov/wp-content/uploads/2018/08/The-National-Nanotechnology-Initiative-Supplement-to-the-President%E2%80%99s-2019-Budget.pdf>
- Papoulis, Dimitrios. (2019). Halloysite based nanocomposites and photocatalysis: A Review. *Applied Clay Science*. 168. 164-174. 10.1016/j.clay.2018.11.009.
- President's Council of Advisors on Science and Technology. July 2012. *Report to the President on Capturing Domestic Competitive Advantage in Advanced Manufacturing*. Executive Office of the President. URL: https://www1.eere.energy.gov/manufacturing/pdfs/pcast_july2012.pdf
- President's Council of Advisors on Science and Technology. July 2012. *Report to the President on Capturing Domestic Competitive Advantage in Advanced Manufacturing*. Executive Office of the President. URL: https://www1.eere.energy.gov/manufacturing/pdfs/pcast_july2012.pdf
- Raki, Laila; J. Beaudoin, R. Alizadeh, J. Makar, & S. Tajjiro (2010). Cement and Concrete Nanoscience and Nanotechnology. *Materials*. 3. 10.3390/ma3020918.
- Sanchez, Florence & Sobolev, Konstantin. (2010). Nanotechnology in Concrete - A Review. *Construction and Building Materials*. 24. 2060-2071. 10.1016/j.conbuildmat.2010.03.014.
- Schmid, Otmar & Möller, Winfried & Semmler-Behnke, MA & Ferron, G.A. & Karg, Erwin & Lipka, J & Schulz, Holger & Kreyling, Wolfgang & Stöger, Tobias. (2009). Dosimetry and toxicology of inhaled ultrafine particles. *Biomarkers : biochemical indicators of exposure, response, and susceptibility to chemicals*. 14 Suppl 1. 67-73. 10.1080/13547500902965617.
- Shen, Shihui & Burton, Maria & Jobson, Bertram & Haselbach, Liv. (2012). Shen Title: Pervious Concrete with Titanium Dioxide as a Photocatalyst Compound for a Greener

Urban Road Environment 2 3. Construction and Building Materials. 35.
10.1016/j.conbuildmat.2012.04.097.

United Kingdom Department for Environment, Food and Rural Affairs (DEFRA). 2016. *Paints and Surfaces for the Removal of Nitrogen Oxides*. URL https://uk-air.defra.gov.uk/assets/documents/reports/cat11/1604130958_PB14425_Paints_and_Surfaces_for_the_Removal_of_Nitrogen_Oxides.pdf

United States Government Accountability Office (USGAO). May 2010. *Nanotechnology: Nanomaterials Are Widely Used in Commerce, But EPA Faces Challenges in Regulating Risk*. GAO Report 10-549. URL <https://www.gao.gov/products/GAO-10-549>

-----USGAO. May 2012. *Nanotechnology: Improved Performance Needed for Environmental, Health and Safety Research*. GAO Report No. 12.427. URL: <https://www.gao.gov/products/GAO-12-427>

-----USGAO. January 2014. *Nanomanufacturing: emergence and Implications for U.S. Competitiveness, the Environment and Human Health: Highlights of a Forum*. GAO Report 14-181SP. URL <https://www.gao.gov/products/GAO-14-181SP>

-----USGAO. May 2014. *Nanomanufacturing and U.S. Competitiveness: Challenges and Opportunities*. GAO Report 14-618T. URL <https://www.gao.gov/products/GAO-14-618T>

Appendix A

Table A1: Journal Articles on Nanotechnology

	Author(s)	Title	Year	Journal	DOI Number or URL
1	Fabjola Bilo, Alessandra Zanoletti, Laura Borgese, Laura E. Depero, and Elza Bontempi	Chemical Analysis of Air Particulate Matter Trapped by a Porous Material, Synthesized from Silica Fume and Sodium Alginate	2019	Journal of Nanomaterials Volume 2019, Article ID 1732196, 9 pages	https://doi.org/10.1155/2019/1732196
2	D. Papoulis	Halloysite based nanocomposites and photocatalysis: A Review	2019	Applied Clay Science, Vol 168 (February 2019) 164-174	https://doi.org/10.1016/j.clay.2018.11.009
3	L.P. Singha, D. Alia, I. Tyagia, U. Sharma, R. Singha, P. Hou	Durability studies of nano-engineered fly ash concrete	2019	Construction and Building Materials Volume 194, 10 January 2019, Pages 205-215	https://doi.org/10.1016/j.conbuildmat.2018.11.022
4	Alireza Haghighat Mamaghani, Fariborz, Haghighat, Chang-Seo Lee	Hydrothermal/solvothermal synthesis and treatment of TiO ₂ for photocatalytic degradation of air pollutants: Preparation, characterization, properties, and performance	2019	Chemosphere Volume 219, March 2019, Pages 804-825	https://doi.org/10.1016/j.chemosphere.2018.12.029
5	Lin Qiu, Yuxin Ouyang, Yanhui Feng, Xinxin Zhang	Review on micro/nano phase change materials for solar thermal applications	2019	Renewable Energy 140 (2019) 513-538	https://doi.org/10.1016/j.renene.2019.03.088
6	L.P. Singh, D. Ali, I. Tyagi, U. Sharma, R. Singh, P. Hou	Durability studies of nano-engineered fly ash concrete	2019	Construction and Building Materials 194 (2019) 205-215	https://doi.org/10.1016/j.conbuildmat.2018.11.022

	Author(s)	Title	Year	Journal	DOI Number or URL
7	Amal Abdelhaleem, Wei Chu, Xiaoliang Liang	Diphenamid degradation via sulfite activation under visible LED using Fe ⁺³ impregnated N-doped TiO ₂ photocatalyst	2019	Applied Catalysis B: Environmental Volume 244, 5 May 2019, Pages 823-835	https://doi.org/10.1016/j.apcatb.2018.11.085
8	Yonathan Reches	Nanoparticles as concrete additives: Review and Perspectives	2018	Construction and Building Materials 175 (2018) 483-495	https://doi.org/10.1016/j.conbuildmat.2018.04.214
9	L.D. García, J.M. Pastora, J. Peña	Self-cleaning and depolluting glass reinforced concrete panels: Fabrication, optimization and durability evaluation	2018	Construction and Building Materials Volume 162, 20 February 2018, Pages 9-19	https://doi.org/10.1016/j.conbuildmat.2017.11.156
10	Maria Kaszynska, and Norbert Olczyk	The Influence Of TiO ₂ Nanoparticles on the Properties of Self-Cleaning Cement Mortar	2018		https://doi.org/10.5593/sgem2018/6.3
11	Jing Li, Danzhen Zhang, Tingting Yang, Shen Yang, Xudong Yang, Hongwei Zhu	Nanofibrous membrane of graphene oxide-in-polyacrylonitrile composite with low filtration resistance for the effective capture of PM2.5	2018	Journal of Membrane Science 551 (2018) 85-92	https://doi.org/10.1016/j.memsci.2018.01.025
12	J. Nayak, A.K. Mohapatra, and H. Kim	Effects of Surface Carbon on the Visible-light Photocatalytic Activity of Nitrogen Doped TiO ₂ -C Nanocomposite Powder	2018	Current Nanoscience, 2016, 12, 365-371	
13	Aiqin Mao, Peipei Ding, Feng Quan, Tianchi Zhang, Xueqin Ran, Yibu Li, Xia Jin, Xiaolong Gu	Effect of aluminum element on microstructure evolution and properties of multicomponent Al-Co-Cr-Cu-Fe-Ni nanoparticles	2018	Journal of Alloys and Compounds Volume 735, 25 February 2018, Pages 1167-1175	https://doi.org/10.1016/j.jallcom.2017.11.233

	Author(s)	Title	Year	Journal	DOI Number or URL
14	Young Kyu Kim, Seong Jae Hong, Hyung Bae Kim, and Seung Woo Lee	Evaluation of In-Situ NO _x Removal Efficiency of Photocatalytic Concrete in Expressways	2018	KSCE Journal of Civil Engineering (2018) 22(7):2274-2280	10.1007/s12205-017-0028-9
15	Seunghyun Weon, Eunji Choi, Hyejin Kim, Jee Yeon Kim, Hee-Jin Park, Sae-mi Kim, Wooyul Kim, and Wonyong Choi	Active Facet Exposed TiO ₂ Nanotubes Photocatalyst Filter for Volatile Organic Compounds Removal: From Material Development to Commercial Indoor Air Cleaner Application	2018	Environmental Science and Technology 2018, 52 9330-9340	
16	Adriana C. Mera, A. Martínez-de la Cruz, E. Pérez-Tijerina, M.F. Meléndrez, Héctor Valdése	Nanostructured BiOI for air pollution control: Microwave-assisted synthesis, characterization and photocatalytic activity toward NO transformation under visible light irradiation	2018	Materials Science in Semiconductor Processing Volume 88, December 2018, Pages 20-27	https://doi.org/10.1016/j.mssp.2018.04.045
17	Zhen Lenga, Huayang Yu, Zheming Gao	Study on air-purifying performance of asphalt mixture specimens coated with titanium dioxide using different methods	2018	International Journal of Pavement Research and Technology xxx (2018)	https://doi.org/10.1016/j.ijprt.2018.08.003
18	Zu Wen and Dehong Xia	A thermodynamics model for morphology prediction of aluminum nano crystals fabricated by the inert gas condensation method	2018	Nanotechnology 29, 125301	https://doi.org/10.1088/1361-6528/aaa84d
19	Maria Kaszynska, Norbert Olczyk	The Influence of TiO ₂ Nanoparticles on the Properties of Self-Cleaning Cement Mortar	2018	Section Green Buildings Technologies and Materials	https://doi.org/10.5593/sgem2018/6.3

	Author(s)	Title	Year	Journal	DOI Number or URL
20	Peng Zhang, Dongyang Wan, Zhenyi Zhang, Guodong Wang, Junhua Hu, Guosheng Shao	RGO-functionalized polymer nanofibrous membrane with exceptional surface activity and ultra-low airflow resistance for PM 2.5 filtration	2018	Environ. Sci.: Nano, (2018) 5, 1813	https://doi.org/10.1039/c8en00468d
21	Xiao Chen, Zhenglong Zhao, Ying Zhou, Qiulian Zhu, Zhiyan Pana, Hanfeng Lu	A facile route for spraying preparation of Pt/TiO ₂ monolithic catalysts toward VOCs combustion	2018	Applied Catalysis A: General Volume 566, 25 September 2018, Pages 190-199	https://doi.org/10.1016/j.apcata.2018.08.025
22	Vinita Vishwakarma, and D. Ramachandran	Green concrete mix using sold waste and nanoparticles as alternatives—A review	2018	Construction and Building Materials 162 (2018) 96-103	https://doi.org/10.1016/j.conbuildmat.2017.11.174
23	Thomas A.J Kuhlbusch, Susan W.P Wijnhoven, and Andrea Haase	Nanomaterial exposures for worker, consumer and the general public	2018	NanoImpact 10 (2018) 11-25	
24	Rodolphe Carpentier, Anne Platel, Helena Maiz-Gregores, Fabrice Nessler, and Didier Betbeder	Vectorization by nanoparticles decreases the overall toxicity of airborne pollutants	2018	PLoS ONE 12 (8) e0183243	https://doi.org/10.1371/journal.pone.0183243
25	Xiaohui Tang, Jean-Pierre Raskin, Driss Lahem, Arnaud Krumpmann, André Decroly, and Marc Debliquy	A Formaldehyde Sensor Based on Molecularly-Imprinted Polymer on a TiO ₂ Nanotube Array	2017	Sensors 2017, 17, 675;	https://doi.org/10.3390/s17040675
26	Boris Mahltig and Haoqian Miao	Microwave-assisted preparation of photoactive TiO ₂ on textile substrates	2017	J. Coat. Technol. Res., 14(3) 721–733, 2017	https://doi.org/10.1007/s11998-016-9891-4

	Author(s)	Title	Year	Journal	DOI Number or URL
27	Yanjia Yu, Junmin Wana, Ziang Yang, and Zhiwen Hu	Preparation of the MoS ₂ /TiO ₂ /HMFs ternary composite hollow microfibres with enhanced photocatalytic performance under visible light	2017	Journal of Colloid and Interface Science Volume 502, 15 September 2017, Pages 100-111	https://doi.org/10.1016/j.jcis.2017.04.058
28	N.B. Singh, Meenu Kalra, and S.K. Saxena	Nanoscience of cement and concrete	2017	Materials Today: Proceedings 4 (20147) 5478-5487	
29	Hosseini Mohammadhosseini, Jamaludin Mohamad Yatim, Abdul Rahman Modh Sam, and A.S.M Abdul Awal	Durability performance of green concrete composites containing waste carpet fibers and palm oil fuel ash	2017	Journal of Cleaner Production 144 (2017) 448-458	
30	M.S. Muhd Norhasri, M.S. Hamidah, and A Mohd Fadzil	Applications of using nano materials in concrete: A review	2017	Construction and Building Materials 133 (2017) 91-97	http://dx.doi.org/10.1016/j.conbuildmat.2016.12.005
31	Shen Yang, Zhenxing Shu, Fei Wei, and Xudong Yang	Carbon nanotubes/activated carbon fiber-based air filter media for simultaneous removal of particulate matter and ozone	2017	Building and Environment 125 (2017) 60-66	http://dx.doi.org/10.1016/j.buildenv.2017.08.040
32	Anwar M. Mohamed	Influence of nano materials on flexural behavior and compressive strength of concrete	2016	HBRC Journal (2016) 12, 212-225	http://dx.doi.org/10.1016/j.hbrcj.2014.11.006
33	Marisol Faraldos and Ana Bahamonde	Environmental applications of titania-graphene photo catalysts	2017	Catalysis Today 285 (2017) 13-28	http://dx.doi.org/10.1016/j.cattod.2017.01.029
34	N.B. Singh, Meenu Kalra, and S.K. Saxena	Nanoscience of Cement and Concrete	2017	Materials Today: Proceedings 4 (2017) 5478–5487	

	Author(s)	Title	Year	Journal	DOI Number or URL
35	D.E. Macphee and A. Folli	Photocatalytic concretes—The interface between photo catalysis and cement chemistry	2016	Cement and Concrete Research 85 (2016) 48–54	http://dx.doi.org/10.1016/j.cemconres.2016.03.007
36	Anwar M. Mohamed	Influence of nano materials on flexural behavior and compressive strength of concrete	2016	Housing and Building National Research Center Journal 12 (2016) 212-225	http://dx.doi.org/10.1016/j.hbrcj.2014.11.006
37	J Nayak, A. K. Mohapatra, and H. Kim	Effects of Surface Carbon on the Visible-light Photocatalytic Activity of Nitrogen Doped TiO ₂ -C Nanocomposite Powder	2016	Current Nanoscience 12 (2016) 365-371	
38	Giampiccolo, Andrea; Ansell, Martin; Tobaldi, David; & Ball, Richard	Synthesis of Co–TiO ₂ nanostructured photocatalytic coatings for MDF substrates	2016	Institution of Civil Engineers: Green Materials, vol. 4, no. 4, pp. 1-10.	https://doi.org/10.1680/jgrma.16.00004
39	Ataallah Nadiri, Marwa M. Hassan, and Somayeh Asadi	Supervised Intelligence Committee Machine to Evaluate Field Performance of Photocatalytic Asphalt Pavement for Ambient Air Purification	2015	Transportation Research Record: Journal of the Transportation Research Board, No. 2528, Transportation Research Board, Washington, D.C., 2015, pp. 96–105.	https://doi.org/10.3141/2528-11

	Author(s)	Title	Year	Journal	DOI Number or URL
40	Jiaqiang Wang, Encai Ou, Junjie Li, Xiaoyun Yang, Wei Wang, Zhiying Yann, and Cong Li	Synthesis of mesoporous titania–graphite composite emplatd by hypocrellins for visible-light photocatalytic degradation of acetaldehyde	2015	Materials Science in Semiconductor Processing Volume 31, March 2015, Pages 397-404	https://doi.org/10.1016/j.mssp.2014.12.029
41	Sammy W. Verbruggen	TiO ₂ photo catalysis for the degradation of pollutants in gas phase: From morphological design to plasmonic enhancement	2015	Journal of Photochemistry C: Photochemistry Reviews 24 (2015) 64-82	http://dx.doi.org/10.1016/j.jphotochemrev.2015.07.001
42	Abdalla S. Al-Rawashdeh1 and Shad Sargand	Performance Assessment of a Warm Asphalt Binder in of Water by Using Surface Free Energy Concepts and Nanoscale Techniques	2014	American Society of Civil Engineers	http://dx.doi.org/10.1061/(ASCE)MT.1943-5533.0000866
43	Somayeh Asadi, Marwa Hassan, John T. Kevern, and Tyson Rupnow	Nitrogen Oxide Reduction and Nitrate Measurements on TiO ₂ photocatalytic Pervious Concrete pavement	2014	International Journal of Pavement Research and technology Vol. 7 No. 4 Jul 2014	10.6135/jiprt.org.tw/2014.7(4).273
44	Heather Dua, Marwa M. Hassan, and Louis J. Thibodeaux	Kinetic Study of Photocatalytic Degradation of Nitrogen Monoxide with Titanium Dioxide Nanoparticles in Concrete Pavements	2014	Transportation Research Record: Journal of the Transportation Research Board, No. 2441 pp 38-45	https://doi.org/10.3141/2441-06
45	Heather Dua and Marwa M. Hassan	Potential of Nanoparticles and Nitrates Released to Water from Photocatalytic Pavements	2014	Construction Research Congress 2014	https://doi.org/

	Author(s)	Title	Year	Journal	DOI Number or URL
46	Aidong Tang, Yanrong Jia, Shiying Zhang, Qumin Yu, Xiangchao Zhang	Synthesis, characterization and photocatalysis of AgAlO ₂ /TiO ₂ heterojunction with sunlight irradiation	2014	Catalysis Communications 50 (2014) 1-4	http://dx.doi.org/10.1016/j.catcom.2014.02.015
47	Elia Boonen and Anne Beeldens	Recent Photocatalytic Applications for Air Purification in Belgium	2014	Coatings 2014 (4, 553-573	https://doi.org/10.3390/coatings4030553
48	David Osborn; Marwa Hassan, Somayeh Asadi, and John R. White	Durability Quantification of TiO ₂ Surface Coating on Concrete and Asphalt Pavements	2014	J. Mater. Civ. Eng., 2014, 26(2): 331-337	http://dx.doi.org/10.1061/(ASCE)MT.1943-5533.0000816
49	Chunya Wang, Peng Li, Yichen Zong, Yingying Zhang, Shuiqing Li, and Fei Wei	A high efficiency particulate air filter based on agglomerated carbon nanotube fluidized bed	2014	Carbon 79 (2014) 424-431	http://dx.doi.org/10.1016/j.carbon.2014.07.086
50	Marwa Hassan, Louay N. Mohammad, Somayeh Asadi, Heather Dylla, and Sam Cooper III	Sustainable Photocatalytic Asphalt Pavements for Mitigation of Nitrogen Oxide and Sulfur Vehicle Emissions	2013	Journal of Materials in Civil Engineering ASCE / March 2013 /365	http://dx.doi.org/10.1061/(ASCE)MT.1943-5533.0000613
51	David Osborn, Marwa Hassan, Somayeh Asadi, and John R. White	Durability Quantification for a TiO ₂ Photocatalytic Concrete and Asphalt Pavements	2013	TRB Annual Meeting	
52	Elia Boonen, Anne Beeldens	Photocatalytic roads: from lab test to real scale applications	2013	Eur. Transp., Res. Rev 6:79-89	https://doi.org/10.1007/s12544-012-0085-6
53	Ozkan Yildiz, Philip D. Bradford	Aligned carbon nanotube sheet high efficiency particulate air filters	2013	Carbon 64 (2013) 295-304	http://dx.doi.org/10.1016/j.carbon.2013.07.066
54	Cameron J. Churchill & Daman K. Panesar	Life-cycle cost analysis of highway noise barriers designed with photocatalytic cement	2013	Structure and Infrastructure Engineering, 9:10, 983-998,	https://doi.org/10.1080/15732479.2011.653574

	Author(s)	Title	Year	Journal	DOI Number or URL
55	Jianzhong Pei, Hongzhao Du Yanwei Li, Fengxu Ma, Qunle Du, and Zin Shi	Experimental Study on nanometer TiO ₂ Doped with Fe ³⁺ for purification Effect of automobile exhaust in the tunnel	2013	TRB Annual Meeting	
56	Jun Chena, Shi-cong Kou, Chi-sun Poon	Hydration and properties of nano-TiO ₂ blended cement composites	2012	Cement and Concrete Composites Volume 34, Issue 5, May 2012, Pages 642-649	http://dx.doi.org/10.1016/j.cemconcomp.2012.02.009
57	G.L. Guerrini, A. Beeldens, M. Crispino, G. D'Ambrosio, and S. Vismara1	Environmental benefits of innovative photocatalytic cementitious road materials	2012	10 th International Conference on Concrete Pavements, July 8-12, 2012	
58	Marwa M. Hassan, Heather Dylla, Somayeh Ashadi, Louay N. Mohammad, and Samuel Cooper	Laboratory Evaluation of Environmental Performance of Photocatalytic Titanium Dioxide Warm-Mix Asphalt Pavements	2012 (a)	Journal of Materials in Civ. Eng., 2012, 24(5): 599-605	http://dx.doi.org/10.1061/(ASCE)MT.1943-5533.0000408
59	Marwa M. Hassan, Heather Dylla, Louay N. Mohammad, and Tyson Rupnow	Methods for the Application of Titanium Dioxide Coatings to Concrete Pavement	2012 (b)	Int. J. Pavement Res. Technol. 5(1):12-20	
60	Marwa M. Hassan, Louay N. Mohammad, Samuel B. Cooper III, and Heather Dylla	Evaluation of Nano-Titanium Dioxide Additive on Asphalt Binder Aging Properties	2012 (c)	TRB Annual Meeting	
61	Zhenan Han, Victor W.C. Chang, Li Zhang, Man Siu Tse, Ooi Kiang Tan, Lynn M. Hildemann	Preparation of TiO ₂ -Coated Polyester Fiber Filter by Spray-Coating and Its Photocatalytic Degradation of Gaseous Formaldehyde	2012	Aerosol and Air Quality Research, 12: 1327-1335,	https://doi.org/10.4209/aaqr.2012.05.0114
62	Jun Chen, Shi-cong Kou, Chi-sun Poon	Hydration and properties of nano-TiO ₂ blended cement composites	2012	Cement and Concrete Composites 34 (2012) 642-649	https://doi.org/10.1016/j.conbuildmat.2011.10.047

	Author(s)	Title	Year	Journal	DOI Number or URL
63	Tao Meng, Yachao Yu, Xiaolian Qian, Shulin Zhan, Kuangliang Qian	Effect of nano-TiO ₂ on the mechanical properties of cement mortar	2012	Construction and Building Materials 29 (2012) 241-245	https://doi.org/10.1016/j.conbuildmat.2011.10.047
64	Shihui Shen, Maria Burton, Bertram Jobson, and Liv Haselbach	Pervious Concrete with Titanium Dioxide as a Photo catalyst Compound for a Greener Urban Road Environment	2012	TRB 2012 Annual Meeting	
65	Marion Schmitt, Heather Dylla, Marwa M. Hassan, Louay N. Mohammad, Tyson Rupnow, and Earle Wright	Impact of Mixed Nitrogen Dioxide (NO ₂) and Nitrogen Oxide (NO) Gases on Titanium Dioxide Photo Degradation of NO _x	2011	T&DI Congress 2011	
66	Vassileios C. Papadimitriou, Vassileios G. Stefanopoulos, Manolis N. Romanias, Panos Papagiannakopoulos, Kyriaki Sambani, Valentin Tudose, and George Kiriakidis	Determination of photo-catalytic activity of un-doped and Mn-doped TiO ₂ anatase powders on acetaldehyde under UV and visible light	2011	Thin Solid Films 520 (2011) 1195-1201	http://dx.doi.org/10.1016/j.tsf.2011.07.073
67	Ali Nazari, Shadi Riahi	The effects of SiO ₂ nanoparticles on physical and mechanical properties of high strength compacting concrete	2011	Composites Part B 42 (2011) 570-578	https://doi.org/10.1016/j.compositesb.2010.09.025
68	Maurizio Crispino, Stefania Vismara, and Claudio Vroveli	Evaluation of Long Term Environmental and Functional Performances of Innovative Photocatalytic Road Pavements	2011	TRB Annual Meeting	

	Author(s)	Title	Year	Journal	DOI Number or URL
69	M. V. Diamanti, F. Bolzoni, M. Ormellese, E. A. Perez-Rosales, and M. P. Pedferri	Characterization of titanium oxide films by potential dynamic polarization and electrochemical impedance spectroscopy	2010	Corrosion Engineering, Science and Technology 2010 Vol 45 No 6	DOI https://doi.org/10.1179/147842208X37319
70	Hyun Ook Seo, Kwang-Dae Kim, Yuan Luo, Myoung Joo Kim, Nilay Kumar Dey, and Young Dok Kim	Interaction of TiO ₂ Films on Carbon Fibers with Toluene	2010	Bull. Korean Chem. Soc.2010, Vol. 31, No. 8 2333I	https://doi.org/10.5012/bkcs.2010.31.8.2333
71	R. Vinu and Giridhar Madras	Environmental remediation by photo catalysis	2010	Journal of the Indian Institute of Science VOL 90:2 Apr–Jun 2010	
72	Laila Raki, James Beaudoin, Rouhollah Alizadeh, Jon Makar, and Taijiro Sato	Cement and Concrete Nanoscience and Nanotechnology	2010	Materials 3 (2010) 918-642	https://doi.org/10.3390/ma3020918
73	Florence Sanchez and Konstantin Sobolev	Nanotechnology in concrete - A review	2010	Construction and Building Materials 24 (2010) 2060-2071	https://doi.org/10.1016/j.conbuildmat.2010.03.014
74	Heather Dylla, Marwa M. Hassan, Louay N. Mohammad, Tyson Rupnow, and Earle Wright	Evaluation of Environmental Effectiveness of Titanium Dioxide Photo catalyst Coating for Concrete Pavement	2010	TRB Annual Meeting	
75	Z. Bittnam, P.J.M. Bartos, J. Nemecek, V. Smilaurer, J. Zemen (Eds)	Nanotechnology in Construction 3	2009	NICOM 3 2009	
77	Gerd Bolte	Innovative building materials – reduction of pollutants with TioCem®	2009	ZKG International No. 1-2009 (Vol 62)	

	Author(s)	Title	Year	Journal	DOI Number or URL
78	Z. Bittnar, P.J.M. Bartos, J. Nemecek, V. Smilauer, J. Zemen (Eds)	Nanotechnology in Construction 3: Proceedings of the NICOM3	2009	NICOM 3	
79	O. Schmid, W. Möller, M. Semmler-Behnke, G. A. Ferron, E. Karg, J. Lipka, H. Schulz, W.G. Kreyling, and T. Stoeger	Dosimetry and Toxicology of Inhaled Ultrafine Particles	2009	Biomarkers, 2009, 14(SI) 67-73	https://doi.org/10.1007/978-3-642-00980-8
80	Qiang Guan, Zhanyu Wang, and Haiyang Bai	Experiment On Efficiency Of Nano Titanium Dioxide Photocatalytic Materials Degrading Factors Of Automotive Emission	2008	American Society of Engineers: Plan Build and Manage Transportation Infrastructure Congress 2007	
81	Toshihiko Nakamura and Seishi Meiarash	Nitrogen Oxides Removal Performance of Carbonized Aggregate Coated with Titanium Dioxide	2001	Transactions of the Materials Research Society of Japan 26 [3] 837-840 (2001)	

Table A2: Journal Items on Non-Nano Techniques for Emissions Reduction

	Author(s)	Title	Year	Journal	DOI Number or URL
1	Lauren Rangel, Vikram Kapoor, Jeffrey Hutchinson, and Samer Dessouky	Carbon Sequestration of Soil and Plants along IH-35 in Bexar County, Texas	2019	MATEC Web of Conferences 271, 04001 (2019)	https://doi.org/10.1051/matecconf/201927104001
2	Dr. Vikram Kapoor, Dr. Jeffrey Hutchinson, Dr. Samer Dessouky	Evaluation and Enhancement of Carbon Sequestration Potential, Bioenergy Production and Ecosystem Services of Existing Vegetation Along Roadsides	2019	Tran-SET	
3	Tim Smedly	Could Wooden Buildings be a Solution to Climate Change	2019	BBC Future	
4	Ines Teotonio, Cristina Matos Silva, Carlos Oliveira Cruz	Eco-solutions for urban environments regeneration: The economic value of green roofs	2018	Journal of Cleaner Production Volume 199, 20 October 2018, Pages 121-135	https://doi.org/10.1016/j.jclepro.2018.07.084
5	E. Luévano-Hipólito, A. Martínez-de la Cruz	Photocatalytic stucco for NO _x removal under artificial and by real weatherism	2018	Construction and Building Materials Volume 174, 20 June 2018, Pages 302-309	https://doi.org/10.1016/j.conbuildmat.2018.04.095
6	L.D. Garcia, J.M. Pastor and J. Pena	Self-cleaning and depolluting glass reinforced concrete panels: Fabrication, optimization and durability evaluation	2018	Construction and Building Materials 162 (2018) 9-196	https://doi.org/10.1016/j.conbuildmat.2017.11.156

	Author(s)	Title	Year	Journal	DOI Number or URL
7	K.V. Abhijith, Prashant Kumar, John Gallagher, Aonghus McNabola, Richard Baldaufe, Francesco Pilla, Brian Broderick, Silvana Di Sabatinoh, Beatrice Pulvirentii	Air pollution abatement performances of green infrastructure in open road and built-up street canyon environments - A review	2017	Atmospheric Environment 162 (2017) 71-86	https://doi.org/10.1016/j.atmosenv.2017.05.014
8	Zhen He; Zhen Li; and Yixin Shao	Effect of Carbonation Mixing on CO ₂ Uptake and Strength Gain in Concrete	2017	J. Mater. Civ. Eng., 2017, 29(10): 04017176	https://doi.org/10.1061/(ASCE)MT.1943-5533.0002031
9	K.M. Liew, A.O. Sojobi, and L.W. Zhang	Green concrete: Prospects and challenges	2017	Construction and Building Materials 156 (2017) 1063-1095	http://dx.doi.org/10.1016/j.conbuildmat.2017.09.008
10	Hossein Mohammad Hosseini, Jamaludin Mohamad Yatim, Abdul Rahman Modh Sam, and A.S.M. Abdul Awal	Durability performance of green concrete composites containing waste carpet fibers and palm oil fuel ash	2017	Journal of Cleaner Production 144 (2017) 448-458	http://dx.doi.org/10.1016/j.jclepro.2016.12.151
11	Byung Kwan Oh, Jun Su Park, Se Woon Choi, and Hyo Seon Park	Design model for analysis of relationships among CO ₂ emissions, cost, and structural parameters in green building construction with composite columns	2016	Energy and Buildings 118 (2016) 301-315	http://dx.doi.org/10.1016/j.enbuild.2016.03.015
12	Tobi Eniolu Morakinyo, Yun Fat Lama, and Song Hao	Evaluating the role of green infrastructures on near-road pollutant dispersion and removal: Modelling and measurement	2016	Journal of Environmental Management Volume 182, 1 November 2016, Pages 595-605	https://doi.org/10.1016/j.jenvman.2016.07.077

	Author(s)	Title	Year	Journal	DOI Number or URL
13	Marinos Karterisa, Ifigeneia Theodoridou, Giorgos Mallinisc, Emmanouel Tsirosa, Apostolos Karterisa	Towards a green sustainable strategy for Mediterranean cities: Assessing the benefits of large-scale green roofs implementation in Thessaloniki, Northern Greece, using environmental modelling, GIS and very high spatial resolution remote sensing data	2016	Renewable and Sustainable Energy Reviews 58 (2016) 510-525	http://dx.doi.org/10.1016/j.rser.2015.11.098
14	Fabrizio Ascione, Nicola Bianco, Rosa Francesca De Masi, Mattheos Santamouris, Giuseppe Peter Vanoli	Energy Performance of Cool-Colors and Roofing Coatings in Reducing Free Solar Gains during the Heating Season: Result of an In-Field Investigation	2016	Procedia Engineering Vol 169 (2016) 375-383	
15	Kim Hung Mo, U. Johnson Alengaram, Modh Zamin Jumaat, Soon Poh Yap, Siew Cheng Lee	Green concrete partially comprised of farming waste residues: a review	2016	Journal of Cleaner Production 117 (2016) 122-138	http://dx.doi.org/10.1016/j.jclepro.2016.01.022
16	Bambang Suhendro	Toward Green concrete for better sustainable environment	2014	Procedia Engineering Vol 95 (2014) 305-320	doi: 10.1016/j.proeng.2014.12.190
17	Saumitra V. Joshia, Sat. Ghosh	On the air cleansing efficiency of an extended green wall: A CFD analysis of mechanistic details of transport processes	2014	Journal of Theoretical Biology Volume 361, 21 November 2014, Pages 101-110	https://doi.org/10.1016/j.jtbi.2014.07.018
18	Diana Sannino, Vincenzo Vaiano, Giuseppe Sarno, Paolo Ciambelli	Smart Tiles for the Preservation of Indoor Air Quality	2013	Chemical Engineering Transactions Vol 32, 2013	https://doi.org/10.3303/CET132060

	Author(s)	Title	Year	Journal	DOI Number or URL
19	Nyuk Hien Wong; Alex Yong Kwang Tan; Puay Yok Tan; Angelia Sia; and Ngian Chung Wong	Perception Studies of Vertical Greenery Systems in Singapore	2010	330 Journal of Urban Planning and Development December 2010	
20	C.S. Poon and E. Cheung	Performance of photo-catalytic paving blocks made from waste	2006	Institute of Civil Engineers Waste and Resource Management 159 (November 2006) 165-171	https://doi.org/10.1680/warm.2006.159.4.165